

3/4" T&G Advantech Underlayment

Thickness	W x L	PS-2 Span Rating	Code Evaluation Report	Edge Profile	Approx. Weight per Panel	Panels per Unit
23/32"	4' x 8'	24 oc	ESR-1785	T & G	78 lbs	45 pcs.



A Lot is Riding On Your Subfloor

Build with AdvanTech® flooring for award-winning performance you can rely on. Specifically engineered to combine industry-leading strength, superior moisture resistance and installation ease, AdvanTech flooring is the FLAT OUT BEST™ for a quiet, stiff floor.

Total performance in one panel:

- High density engineered wood for industry leading strength and stiffness
- Advanced moisture resistant resin technology applied through the panel
- Superb fastener-holding power helps keep floors flat and quiet
- Patented fastening guide for easier installation
- Precisely milled and extremely durable tongue and groove profile for easy installation
- Ranked #1 in quality every year for more than a decade
- Backed by the reputation of Huber Engineered Woods



Precision Engineered

Every step of the manufacturing process is precisely engineered to produce a panel with superior performance and unmatched consistency. Its design values are recognized by the ICC-ES and published in ESR-1785. View them at www.icc-es.org.

What does ESR-1785 mean to you?

- Overall, 62% better design bending strength
- 28% better design bending stiffness than commodity OSB
- 16% better design bending stiffness than commodity plywood
- Overall, 10% better design fastener holding power



Best-In-Class Warranty

Backed by a lifetime limited warranty that is transferable between future homeowners, AdvanTech flooring delivers performance you can trust.



No Sanding Guarantee

AdvanTech panels will stand up to your most demanding jobsites and are backed by a 500-day no-sanding guarantee. Say goodbye to swelling, cupping and delamination.



Voted #1 in Quality

Builders from across the nation have voted AdvanTech flooring #1 in quality every year for over a decade. That's a reputation you can build on.