

Physical Properties

Appearance Black liquid	Drying Time @ 50% R.H. 68°F (20°C) Dry to touch in 4 hours	Solids By Weight 42 - 46%
Application Temperature 50°F (10°C) and rising	Flash Point >212 °F (100°C)	Specific Gravity @ 77° F (25°C) 1.14 - 1.20
Brookfield Viscosity 5000-7500 cPs	Freezability Do not freeze	Weight Per Gallon 9.5 - 10.0 lbs
Color Black brown	Maximum VOC 50 g/l	

Description

DI930 - PROFESSIONAL EASY-TO-STIR RUBBERIZED DWY FILLER & SEALER, a professional grade asphalt driveway coating, is a heavy bodied product formulated to fill and seal cracks up to 1/8" wide. This product cleans up with soap and water when wet. It dries to a rich, matte black, slip resistant finish.

Coverage

Five gallons cover 250 to 300 sq. ft. depending on surface texture and porosity.

Surface Preparation

New blacktop should be weathered 6 months minimum prior to coating. Surface to be coated must be clean and free from dust, dirt, oil, grease, etc. Remove grease and oil deposits with a suitable nonphosphate detergent cleaner and rinse thoroughly with water. Cracks larger than 1/8" and smaller than 1/2" should be repaired with **Do It Pourable Driveway Crack Sealer**. Larger cracks, depressions and chuckholes should be repaired with **Driveway Patch & Crack Filler** or **Driveway Patching Compound**. All repaired areas should be thoroughly cured prior to coating.

Application

Apply when air and surface temperature is at least 50°F and rising and when rain is not likely within 24 hours. Begin application at mid-morning for thorough drying. Stir thoroughly with 2" x 2" board until coating is smooth spreading consistency.

IN HOT WEATHER, USE SPRAY MIST TO KEEP SURFACE DAMP BEFORE APPLICATION. DO NOT LEAVE STANDING WATER. Do not apply on concrete. Do not apply on driveways less than six months old. Do not apply on any surface other than the asphalt surface intended for sealing. Coatings should be applied under normal environmental conditions without thinning.

Precautions

Do not over apply or apply more than one coat. Do not apply if temperature is below 50°F or when temperature will fall below 50°F within 24-48 hours after application. Do not apply if rain is imminent (allow 36-48 hours of rain-free cure). When temperature is above 80°F, dampen driveway with water prior to application. Broom away any puddles. **Do not apply to concrete (only suitable for blacktop surfaces)**. Protect from freezing. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

Cleanup

Clean hands and tools with clean water before emulsion has dried. Dried emulsion can be cleaned with biodegradable terpene solvent.

Caution

CAUTION! Close container after each use. Do not heat container or store at temperatures greater than 120° F. **DO NOT TAKE INTERNALLY!** Use protective measures to avoid contact with eyes and skin. **If swallowed, CALL PHYSICIAN IMMEDIATELY!** **In case of eye contact**, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION.

KEEP OUT OF REACH OF CHILDREN!

KEEP FROM FREEZING!

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

EMPLOYERS should obtain a copy of the **Material Data Safety Sheet (MSDS)** from your supplier or directly from the address below.

Product Sizes

5 GALLON (54.8 lb)

Limited Warranty

The manufacturer warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, is free of defects in material and workmanship for a period of 48 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for such defective product. **THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR PURPOSE, AND THE MANUFACTURER WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.**