

Physical Properties

| | | |
|-----------------------------------|--------------------------------------|--|
| Appearance Black liquid | Freezability Do not freeze | Solids By Weight 30% |
| Color Black-brown | Maximum VOC 25 g/l | Specific Gravity @ 77° F (25°C) 1.08 |
| Flash Point >212°F | Maximum VOS 0.08 lbs/gal | Weight Per Gallon 9.00 - 9.30 lbs. |

Description

DI900 - ASPHALT EMULSION BLACKTOP SEAL ER is an easy to use petroleum asphalt and water emulsion designed for application to new and weathered blacktop pavements in sound condition. Ideal as a topcoat to repaired driveways in which cracks and potholes have been filled and allowed to cure. The sealer improves the appearance and extends the life of the surface. Properly applied, it will not flake, peel, track or crack and dries to a uniform and long lasting jet black finish. Dries to the touch in approximately 4 hours and can be driven on in 24 hours under normal conditions.

Coverage

Five gallons cover 250-400 square feet depending on surface texture and porosity. Coatings should be applied under normal environmental conditions without thinning.

Surface Preparation

Pavement surface should be swept clean of dust and loose stone. Remove grease and oil spots with a scraper to eliminate all traces of oil. Scrub this area with an asphalt driveway cleaner or with detergent and then rinse with water. When dry, use Oil Spot Primer to treat affected areas. Pavement may be flushed with a garden hose. Surface may be left damp, but sweep away all puddles. Repair cracks and small holes up to 1/4 inch wide with Liquid Crack Filler. Follow directions on Crack Filler container. To repair larger cracks (up to 1/2 inch) and for leveling, use Crack Patch. For pot holes 2 ft. wide or larger, use Pot Hole Patch.

Application

Stir thoroughly, 5 to 10 minutes, with a wooden paddle until sealer is of a smooth and uniform consistency. Do not be concerned if the material has a brownish appearance. It will dry to a rich black color when dry. Try to apply sealer early in the day to gain maximum benefit of daytime warmth for drying. Apply material with the brush side of a squeegee or roller. Spread out excess sealer from the surface. Smooth out and remove ridges. Work in a 3 or 4 foot area brushing or rolling in a cross pattern first one way then the other, so all pores are filled. Follow consistent pattern for best appearance.

Precautions

Do not apply two coats in succession. (Never exceed the recommended coverage rate). Do not apply to concrete. When temperature is above 80°F, be sure to dampen driveway prior to application. (Allow 35 to 48 hours of rain-free cure). Driveway may be damp, but not wet during application. Protect from freezing. Apply only when temperature is 50°F and rising. Do not apply when rain is forecasted.

Cleanup

Use clean water before emulsion has dried. Dried emulsion can be cleaned with biodegradable terpene solvent. Tar & Asphalt Remover recommended.

Caution

CAUTION! Close container after each use. Do not heat container or store at temperatures greater than 120°F. Dispose of container and unused contents in accordance with Local, State and Federal regulations.

FOR EXTERIOR USE ONLY!

DO NOT TAKE INTERNALLY!

Use protective measures to avoid contact with eyes and skin. **If swallowed, CALL PHYSICIAN IMMEDIATELY! In case of eye contact** open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **SEEK MEDICAL ATTENTION!**

KEEP OUT OF REACH OF CHILDREN!

KEEP FROM FREEZING!

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from the toll free number or website below.

Product Sizes

5 GALLON (50.8 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**