

Physical Properties

% Non-Volatile, by weight 58 - 63 %	Color black	Stormer Viscosity 50 - 80 sec.
Appearance black liquid	Maximum VOC 250 g/l	Weight Per Gallon 7.8 - 8.4
Behavior @ 140° F (60°C) No blistering / sagging /sliding	Specific Gravity @ 77° F (25°C) .94 - 1.01	

Description

DI300 - FIBERED ASPHALT FOUNDATION COATING may be used to dampproof exterior concrete and masonry walls and foundations.

NOT TO BE SOLD IN SOUTHERN CALIFORNIA.

Coverage

Coverage is approximately 1.5 gallons per 100 sq. ft. depending on texture and porosity of surface.

Surface Preparation

THE SURFACE MUST BE COMPLETELY DRY AND FULLY CURED PRIOR TO APPLICATION. For "green", uncured, or damp concrete surfaces, use Asphalt Emulsion Foundation Coating. Clean dirt, oil, water repellent compounds, laitance, and loose particles from surface. For best results, fill all holes, cracks and joints with cement mortar so the surface is as smooth as possible. Allow cement mortar to fully cure. For best results, apply at room temperature. This product is ready to use. Protect newly exposed surfaces as much as possible.

Application

Stir in container and apply by brush. In cold weather, keep unopened can in a warm room for approximately 24 hours before applying.

Exterior Below Grade Application: Apply a small quantity of **DI300 - FIBERED ASPHALT FOUNDATION COATING** and brush well in both directions, spreading evenly. Work an area about ten feet by five feet. Apply two coats at a rate of 1.5 gallons per 100 square feet per coat. Allow each coat to dry completely before applying second coat or backfilling with dirt. Coating will not dry unless exposed to air.

Important: No dampproof coating will work if it is damaged or scraped off when backfilling, or if the foundation wall itself cracks. If hydrostatic water head is present, please contact Henry Company at the address below for more information on application. Coating should be applied under normal environmental conditions without thinning.

Precautions

FOR EXTERIOR USE ON FOUNDATIONS ONLY. Do not use in interior or enclosed areas. DO NOT apply if there is a threat of rain within 24 hours after application. Keep product in a heated room until ready to use since the coating will thicken in cold weather. Do not apply over damp or wet surfaces. Do not heat container or store at temperatures greater than 110°F. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur. **CLOSE AIR INTAKES UNTIL SOLVENTS DISSIPATE!**

Cleanup

Tools may be cleaned with mineral spirits. Use care in handling solvents. Clean hands with a waterless hand cleaner.

Caution

WARNING! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F. **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! **USE ONLY WITH ADEQUATE VENTILATION!** Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN!

This product contains detectable amounts of chemicals known to the State of California to cause cancer or birth defects or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from the toll free number or address below.

Product Sizes

5 GAL/18.93 L (45.35 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**