

## L-Angle

### 2" x 2" standard L-Angle

A standard 10'-0" long galvanized steel product, which is often field cut to job site conditions for the ultimate use as a connector for framing members. On interior framing it is often used to secure drywall at corner intersections or along horizontal planes. It can also be used as a half track in chase and furred walls.

#### Product Data & Ordering Information:

Material: All Non-Structural Material: Grade 33ksi min. yield strength, G40  
18mils: 25 Gauge, 0.0188" Design Thickness, 0.0179" Min. Thickness  
30mils: 20ga DW, 0.0312" Design Thickness, 0.0296" Min. Thickness

All Structural Material: Grade 33ksi min. yield strength, G60  
33mils: 20ga STR, 0.0346" Design Thickness, 0.0329" Min. Thickness  
43mils: 18 Gauge, 0.0451" Design Thickness, 0.0428" Min. Thickness  
54mils: 16 Gauge, 0.0566" Design Thickness, 0.0538" Min. Thickness  
68mils: 14 Gauge, 0.0713" Design Thickness, 0.0677" Min. Thickness  
97mils: 12 Gauge, 0.1017" Design Thickness, 0.0966" Min. Thickness

Dimensions: 2" leg x 2" leg angle

Stock Lengths: 10'-0" long (Custom lengths available by special orders)

#### ASTM & Code Standards:

- Structural framing is produced to meet or exceed ASTM C955
- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003
- MSDS & Product Certification Information is available at [www.clarkdietrich.com](http://www.clarkdietrich.com)

#### Related Accessories:

- ClarkDietrich SwiftClip L-Series Clips

#### 05.40.00 (Cold-Formed Metal Framing)



#### Used in framing applications:

- Framing connections
- Corner intersections
- Half track connections

#### GREEN Benefits and Recycled Content:

**LEED Credit MR 2** - ClarkDietrich products are manufactured from cold-formed steel. Steel is 100% recyclable, which helps divert debris from the waste stream. The contribution to LEED must be calculated by the contractor based on weight or volume.

**LEED Credit MR 4** - ClarkDietrich's steel products have a minimum recycled content of 34.9%, of which 24.3% is post-consumer, and 9.4% is pre-consumer. To report a higher number for your project or seek Credit MR 5, contact Technical Services at 888-437-3244 or visit [www.clarkdietrich.com](http://www.clarkdietrich.com).

CD-200L-Angle © 04/11 ClarkDietrich Building Systems

#### Project Information

Name: cavobuilderssupplies.com

Address:

#### Contractor Information

Name:

Contact:

Phone:

Fax:

#### Architect Information

Name:

Contact:

Phone:

Fax: