



# USG DUROCK™ BRAND GLASS-MAT TILE BACKERBOARD

- Lightweight and easy to score, snap and fasten
- Moisture- and mold-resistant substrate
- Scores the highest achievable rating (10 out of 10) for mold resistance according to ASTM D3273
- Proprietary cementitious coating provides exceptional tile bond performance

## DESCRIPTION

USG Durock™ Brand Glass-Mat Tile Backerboard is a moisture- and mold-resistant gypsum panel with a fiberglass mat facer and back. The face of the panel is treated with a patented cementitious coating for moisture resistance and enhanced tile bond, making it ideal as a tile substrate for wet areas Res1, Res2, Res3, Com1, Com2 and Com3 as defined by the *Tile Council of North America Handbook 2014*. USG Durock™ Glass-Mat Tile Backerboard combines the tile bond of cement board with the handling and ease of use of a USG Sheetrock® Brand panel. The 5/8" Type X panels are UL classified as fire resistant.

## PRODUCT DATA

Size (thickness x width x length) <sup>1</sup>	Units (pcs) <sup>1</sup>
1/2" x 4' x 8'	50
5/8" x 4' x 8'	40

1. Shipped in units as shown.

## STANDARDS

USG Durock™ Glass-Mat Tile Backerboard exceeds ASTM C1178, which is the standard specification for coated glass-mat water-resistant gypsum backing panels.

## AVAILABILITY

USG Durock™ Glass-Mat Tile Backerboard is distributed throughout the United States. Contact a USG sales office or representative for additional information.

## COMPOSITION AND MATERIALS

USG Durock™ Glass-Mat Tile Backerboard consists of a treated water-resistant gypsum core that is covered with a coated fiberglass mat facer and back and has a proprietary cementitious surface. The panels are square edge.

## DELIVERY AND STORAGE

All materials should be delivered and stored in their original packaging and stored in an enclosed shelter providing protection from damage and exposure to the elements. Store all panels flat.

## ENVIRONMENTAL CONDITIONS

In cold weather and during USG Durock™ Glass-Mat Tile Backerboard and tile installation, temperatures within the building shall be maintained within the range of 40 to 100°F. Adequate ventilation shall be provided to carry off excess moisture. Low temperatures and high relative humidity will increase the time needed.

## INTERIOR APPLICATIONS

Wood framing shall approximate the moisture content it will reach in service by allowing the enclosed building to stand as long as possible prior to the application of the backerboard. Panels are not intended for constant exposure to water. Protect from immersion in water and the eroding effects of cascading water.

## INSTALLATION

- 
- A. Install backerboard with ends and edges closely abutted but not forced together. Stagger end joints in successive courses.
  - B. For flooring applications over a wood-based substrate, laminate USG Durock™ Glass-Mat Tile Backerboard to subfloor using Type 1 organic adhesive or latex-modified thin-set mortar suitable for bonding cement board. Fasten to subfloor with 1-1/4" USG Durock™ Brand Tile Backer Screws for wood framing (or equivalent) or 1-1/2" hot-dipped galvanized roofing nails spaced 8" o.c. in both directions with perimeter fasteners at least 3/8" and less than 5/8" from ends and edges. Drive nails and screws so bottoms of heads are flush with panel surface to ensure firm panel contact with subfloor. Do not overdrive fasteners. Prefill joints with tile-setting mortar or adhesive and then immediately embed USG Durock™ Brand Tile Backer Tape and level joints.
  - C. For wall application, fasten USG Durock™ Glass-Mat Tile Backerboard to framing with specified fasteners. Drive fasteners into field of panels first, working toward ends and edges. Hold panels in firm contact with framing while driving fasteners. Space fasteners maximum 8" o.c. for walls, 6" o.c. for ceilings, with perimeter fasteners at least 3/8" and less than 5/8" from ends and edges. Drive nails and screws so bottoms of heads are flush with panel surface. Do not overdrive fasteners. Approved fasteners include: USG Durock™ Tile Backer Screws for steel framing (or equivalent), 1-1/4" and 1-5/8" for 14- to 20-gauge steel framing; USG Durock™ Tile Backer Screws for wood framing (or equivalent), 1-1/4", 1-5/8" and 2-1/4" for wood framing; and nails (1-1/2" hot-dipped galvanized roofing nails). Prefill joints and then immediately embed USG Durock™ Tile Backer Tape and level joints. Maintain 1/4" gap between USG Durock™ Glass-Mat Tile Backerboard and tub surround.
  - D. Panels should be cut to size with a knife and straight edge. A power saw should be used only if it is equipped with a dust-collection device. Installer should wear NIOSH/MSHA-approved dust mask.
  - E. If waterproofing is required, treat joints and fastener penetrations with USG Durock™ Brand Waterproofing Membrane or equivalent ANSI A118.10 waterproofing membrane. Refer to the current USG Durock™ Brand Waterproofing Membrane submittal sheet (CB595) or waterproofing membrane manufacturer's installation recommendations. For technical assistance, call USG Technical Service at 800 874-4968.
  - F. In areas where standing water could occur on horizontal surfaces, such as shower benches or niches, waterproofing is required with USG Durock™ Waterproofing Membrane or equivalent ANSI A118.10 waterproofing membrane. Refer to the current USG Durock™ Brand Waterproofing Membrane submittal sheet (CB595) or waterproofing membrane manufacturer's installation recommendations.
- 

## LIMITATIONS

1. Tile must be applied on the cementitious (gray)-coated side of panel. Panels are designed for interior use only and should not be used around fireplaces or areas where prolonged exposure to heat exceeds 125°F (52°C) or for exterior applications. Use framing or furring when applying over concrete or masonry block. Install vapor retarders suitable for bonding tiles on the face of the panels.
2. For wall applications, maximum stud spacing: 16" o.c. (24" o.c. for cavity shaft wall assembly). Framing shall be designed (based on stud properties alone) not to exceed L/360 deflection for tile and thin brick. Maximum fastener spacing: 8" o.c. for wood and steel framing; 6" o.c. for ceiling applications.
3. For floor applications, maximum joist spacing 24" o.c. The subfloor system should be designed with a maximum deflection limit of L/360 for the span. Some finish materials may require a more rigid subassembly (such as large format tile and natural stone products). In these cases, follow the manufacturer's minimum requirements. The subfloor shall be APA Span-Rated Plywood or OSB with an Exposure 1 classification or better with tongue and groove or back blocked at the unsupported edges.
4. Maximum dead load for ceiling system is 7.5 psf.
5. Steel framing must be 20-gauge equivalent or heavier.
6. Do not use drywall screws or drywall nails. Do not use drywall joint tape.
7. Do not use with vinyl flooring or over a concrete subfloor.
8. USG Durock™ Glass-Mat Tile Backerboard is not designed for use as a structural panel.
9. Panels should not be used in select wet areas including commercial saunas or steam rooms, gang showers, or shower pan bases.
10. Waterproofing membrane must be used over USG Durock™ Glass-Mat Tile Backerboard in select wet areas including indoor hot tub decks, shower benches and niches, tiled wall and ceiling applications in indoor pool areas, and tiled wall and ceiling applications in residential steam rooms, per ANSI A118.10.

## TECHNICAL DATA

Property	Unit of Measure	Test Method	5/8" USG Durock™ Brand Glass-Mat Tile Backerboard Type X	1/2" USG Durock™ Brand Glass-Mat Tile Backerboard
<b>Weight</b>	psf	ASTM C473	2.5	1.7
<b>Flexural strength</b>	lb	ASTM C473	>140 (perpendicular) >100 (parallel)	>100 (perpendicular) >80 (parallel)
<b>Nail pull</b>	lb (0.25" head diameter)	ASTM C473	>90	>70
<b>Shear bond strength</b>	psi	ANSI A118.1/ANSI A118.4/ANSI A136.1	>50	>50
<b>Surface-burning characteristics</b>	Flame spread/ smoke developed	ASTM E84	15/5	15/5
<b>Fire resistance</b>	—	—	Type X	—
<b>Thermal resistance</b>	hr-°F-ft²/Btu	ASTM C518	0.44	0.42
<b>Mold resistance</b>	—	ASTM D3273	10	10
<b>Floor system service rating</b>	Service rating	ASTM C627	See table below	See table below
<b>Minimum bending radius</b>	ft	—	20	12
<b>Smoke toxicity</b>	Toxicity index	NES 713	0.03 (No toxic gases)	0.03 (No toxic gases)
<b>VOC</b>	Pass/fail	CDPH V1.1	Pass	Pass
<b>Permeability</b>	Perm	ASTM E96 Procedure A	<1	<1.5

## FLOOR SYSTEM SERVICE RATING

TESTED AT THE TILE COUNCIL  
OF NORTH AMERICA PER ASTM C627

	Tile Size		
	2"x2"	6"x6"	8"x8"
<b>Joist spacing (inches on center)</b>	2"x2"	6"x6"	8"x8"
<b>16</b>	Residential	Light commercial	—
<b>19.2</b>	Residential	Light commercial	—
<b>24</b>	—	—	Light commercial

## SUBMITTAL APPROVALS

### PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

### CAUTION

Dust may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Cut and trim with a utility knife or hand saw to minimize dust levels. Power tools must be equipped with a dust-collection system. Wear eye, skin and respiratory protection if necessary. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, call a physician. Do not swallow. If swallowed, call a physician.

For more information call Product Safety: 800 507-8899 or see the SDS at usg.com.

**KEEP OUT OF REACH OF CHILDREN.**

### TRADEMARKS

The trademarks USG, DUROCK, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

### NOTE

Products described here may not be available in all geographic markets. Consult your USG sales office or representative for information.

### NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

### SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

<b>Job Name</b>	
<b>Contractor</b>	<b>Date</b>

800 USG.4YOU  
800 (874-4968)  
usg.com

Manufactured by  
United States Gypsum Company  
550 West Adams Street  
Chicago, IL 60661

CB691/rev. 5-15  
© 2015 USG Corporation and/or  
its affiliates. All rights reserved.  
Printed in U.S.A.

**USG**  
IT'S YOUR WORLD. BUILD IT.™