



## Guardian Unfaced Fiberglass Insulation



### Description:

An unfaced fiberglass thermal/sound attenuation blanket with no vapor barrier. Designed to fit between studs by friction.

### Standard Specifications:

This product has been tested and complies with: ASTM C665, Type I, ASTM E84, Flame Spread <25, Smoke Developed <50. ASTM E136 UL Listing BZJZ.R9602; BKNV.R9602 UL 181.

### Sizes Available:

R-Value	Thickness	W x L	BATTS or ROLL	#PCS/BG	SF/PKG.	CODE
R-11	3-1/2"	16" x 96"	BATTS	20	213	GC7
R-11	3-1/2"	24" x 96"	BATTS	20	288	GC45
R-13	3-5/8"	15" x 94"	BATTS	9	88.12	GT120
R-15	3-5/8"	15" x 47"	BATTS	18	88.12	GR706
R-19	6-1/4"	16" x 96"	BATTS	10	106.67	GC53
R-19	6-1/4"	24" x 96"	BATTS	8	160	GC54
R-21	5-1/2"	15" x 47"	BATTS	12	58.75	GR736
R-21	5-1/2"	23" x 47"	BATTS	12	90.08	GR737
R-25	8"	24" x 48"	BATTS	14	112	GR115
R-30	9-1/2"	16" x 48"	BATTS	10	53.30	GR106
R-30	9-1/2"	24" x 48"	BATTS	10	80	GT107
R-38	12"	16" x 48"	BATTS	8	42.67	GR223
R-38	12"	24" x 48"	BATTS	8	64	GR224