

Issue Date: September 3, 2009 Page 1 of 4

Page 1 of 4	
Section I – Identification	
Product Identification: Cellulose Based Fiber Board	
Product Name: 440 Homasote, 440 Sound Barrier (S/B) PINacle440, ComfortBase, 4-V Floor Deck, Burlap Panel, Easy-Ply Roof Deck, Homex 300, Ice Deck, N Cork Panel, DesignWall440	
Product Use/application: Building Material	
Company: Homasote Company	
P.O. Box 7240	
West Trenton, NJ, 08628-0240	
Contact Numbers:	
Toll Free: 800-257-9491 Ext. 1500. Telephone: 609-883-3300. Fax: 609-40 Website: www.homasote.com	6-9263
Section II – Composition/Information on Ingredients	
Cellulose based material containing 1 to 2% paraffin wax, CAS 8002-74-2, and less that	n 0 1%
copper base pesticide, CAS 39290-85-2. The product contains no known hazardous or carcinogenic components.	
Section III – Hazards Identification	
Routes of Entry: skin contact, eye contact and inhalation of dust	
Health Effects	
Inhalation: nasal dryness and mild irritation	
Eye contact: dryness and mild irritation	
Skin contact: can cause minor irritation and dryness	
Section IV – First Aid Measures	
Inhalation: Move the individual to a dust-free area. Seek medical attention if persis	tent
coughing or difficult breathing develops.	
Skin Contact: Wash with soap and water. Get medical attention if irritation dev	elops or
persists. Eye Contact:Treat as a foreign object. Flush eyes with water.	
· · · · · · · · · · · · · · · · · · ·	
Section V – Fire Fighting Measures	
Material is flammable, not explosive	
Extinguishing Media: Water, carbon dioxide (CO ₂)	
Special Risks: Combustion produces irritating and toxic fumes and	
including carbon monoxide (CO) and carbon dioxide (CO ₂). Dust may ϵ	explode
at concentrations greater than 40 grams dust per cubic meter of air.	
Special Protective Equipment: Self contained breathing apparatus recommended.	
Section VI – Accidental Release Measures	
No health related procedures required. Avoid or control conditions that could result in f	ire.
Reproduce locally) Page 1	



Issue Date: September 3, 2009 Page 2 of 4

Section VII – Handling and Stora	ge		
No health related procedures required. Avoid or control conditions that could result in fire.			
Section VIII – Exposure Controls/Personal Protection			
Descend Protective Equipments re	versional for conding, couring, and other		
Personal Protective Equipment: recommended for sanding, sawing, and other machining			
Respiratory Protection: dust mask and local exhaust			
Eye Protection:safety glassesHand Protection:as required for mechanical operations			
Industrial Hygiene: Follow norn required.	nal work hygiene practices. No special practices		
Section IX – Physical and Chemi	cal Properties		
Form: solid board	Color: gray		
Odor: none	pH: na		
Melting Point: na	Boiling Point: na		
Ignition Temperature: 450 ° F	Flash Point: na		
Density: 20 to 30 lb/ft ³	Solubility in water: negligible		
	rams of dust per cubic meter air for cellulose dust		
Explosion Limit – Upper: unkr	nown		
Section X – Stability and Reactiv			
Conditions to be Avoided: Cond			
Substance to be Avoided: none			
Hazardous Decomposition Product(s): Burning produces irritating and toxic smoke and fumes including paraffin wax fumes, carbon monoxide, and carbon dioxide.			
Section XI – Toxicological Inform	nation		
no known toxicological effects			
Section XII – Ecological Informat	ion		
Significant ecotoxic effects are not exped			
Contian XIII - Dianagal Consider			
Section XIII – Disposal Considera Dispose in accordance with local, state,	federal, and provincial environmental regulations.		
Section XIV – Transportation Information			
Road/Rail: not regulated by DOT			



Issue Date: September 3, 2009 Page 3 of 4

Section XV – Regulatory Information

CERCLA: This product does not contain any chemicals subject to reporting as a CERCLA hazardous substance under 40 CFR 302.4

EPCRA: This product does not contain any chemicals subject to reporting as a toxic chemical under EPCRA Section 313.

CIS R(isk) Phrases:

- R 10: Flammable
- R 43: May cause sensitization by skin contact
- R 66: Repeated exposure may cause skin dryness or cracking

CIS S(afety) Phrases:

- S 15: Keep away from heat
- S 16: Keep away from sources of ignition
- S 17: Keep away from combustible material
- S 22: Do not breathe dust
- S 38: In case of insufficient ventilation, wear suitable respiratory equipment
- S 41: In case of fire, do not breathe fumes.

Section XVI – Other Information

HMIS Ratings:

Health	1	slight hazard
Flammability	0	minimal hazard
Reactivity	0	minimal hazard

minimal I	hazard
	minimal

Safety Officer Telephone No:	609-883-3300, X1188
Safety Officer Fax No:	609-530-1584
Safety Officer 24hr Telephone No:	609-883-3300

List of Acronyms

ACGIH	American Conferences of Governmental Industrial Hygienists
CAS(RN)	Chemical Abstracts (Registry Number)
CERCLA	Comprehensive Emergency Response, Compensation, and Liability
	Act
CIS	International Occupational Safety and Health Information Center
EPCRA	Emergency Planning and Community Right-to-Know Act
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IDLH	Immediately Dangerous to Life or Health (NIOSH)
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	OSHA Permissible Exposure Limit
TLV	Threshold Limit Values (Registered Trademark of ACGIH)
TWA	Time Weighted Average



Issue Date: September 3, 2009 Page 4 of 4

The information contained herein is based on the present state of our knowledge.

The information contained herein characterizes the product with regard to the appropriate safety precautions. The information contained herein does not represent a guarantee of the properties of the product.