FOR ANY EMERGENCY, 24 HOURS / 7 DAYS, CALL: FOR ALL MSDS QUESTIONS & REQUESTS, CALL:

PRODUCT NAME: Wolmanized® µCA-C Treated Wood

1. PRODUCT AND COMPANY IDENTIFICATION

Manufactured By:

REVISION DATE: 09/21/2009 SUPERCEDES: 01/07/2009

MSDS Number: 00000004502 SYNONYMS: None CHEMICAL FAMILY: DESCRIPTION / Treated Wood Products USE: FORMULA: None established

2. HAZARDS IDENTIFICATION

OSHA Hazard
Classification:Wood dust is classified as: carcinogenic, possible sensitizer,
mild skin irritant, possible respiratory irritant., WARNING! MAY
FORM COMBUSTIBLE DUST CONCENTRATIONS IN AIR
(DURING PROCESSING)

Routes of Entry: Chemical Interactions: Medical Conditions Aggravated:	Inhalation, skin, eyes, ingestion No known or reported interactions. Inhalation of the dust from this material at concentrations above the TLV can aggravate pre- existing upper respiratory and lung diseases such as bronchitis, emphysema and asthma., Skin diseases
	including eczema and sensitization

Human Threshold Response Data

Odor Threshold Not established for product.

Irritation Threshold Not established for product.

<u>Classifications</u>				
Hazard Ratings :	<u>Health</u>	Flammability	<u>Physical /</u> Instability	<u>PPI / Special</u> <u>hazard.</u>
HMIS	2*	1	0	
NFPA	2	1	0	

Hazardous Materials Identification System / National Fire Protection Association

Immediate (Acute) Health Effects

Inhalation Toxicity:	Airborne treated or untreated wood dust may cause nose, throat or lung irritation.
Skin Toxicity:	Handling of wood may result in skin exposure to splinters. Prolonged and/or repeated contact with treated or untreated wood dust may result in mild irritation.
Eye Toxicity:	Treated or untreated wood dust may cause mechanical irritation.
Ingestion Toxicity:	Not expected to be a route of exposure in normal industrial use.
Acute Target Organ Toxicity:	Skin, Eyes, Respiratory Tract

Prolonged (Chronic) Health Effects

Carcinogenicity:	IARC has classified untreated hardwood and hardwood/softwood mix wood dust as a Group 1 human carcinogen. The wood dust classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures to untreated wood dust. NTP has classified all untreated wood dust as a carcinogen.
Reproductive and	Not known or reported to cause reproductive or
Developmental Toxicity:	developmental toxicity.
Inhalation:	May cause respiratory sensitization and/or irritation.
Skin Contact:	Treated or untreated wood dust, depending on the species, may cause dermatitis on prolonged, repetitive contact.
Ingestion:	Not expected to be a route of exposure in normal industrial use.
Sensitization:	Various species of untreated wood dust can elicit an allergic respiratory response in sensitized persons. Various species of untreated wood dust can elicit an allergic type skin irritation in sensitized persons.

Chronic Target OrganRespiratory Tract, Skin, EyesToxicity:No additional health information available.Hazard Information :No additional health information available.

3. COMPOSITION / INFORMATION ON INGREDIENTS

CAS OR CHEMICAL NAME	<u>CAS #</u>	<u>% RANGE</u>
Wood Dust	Not Assigned	95 - 99.75
Formaldehyde (by-product of the untreated plywood article)	50-00-0 (Only applies to plywood products)	0 - 0.1
BASIC COPPER CARBONATE	12069-69-1	0.175 - 3.51

4. FIRST AID MEASURES

•

Inhalation:	IF INHALED: Remove individual to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops. If not breathing, give artificial respiration. Call for medical assistance.
Skin Contact:	IF ON SKIN: Flush skin with water for 15 minutes. Take off all contaminated clothing. Seek medical attention if irritation develops.
Eye Contact:	IF IN EYES: Flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation develops.
Ingestion:	IF SWALLOWED: Immediately drink water to dilute. Seek medical attention if symptoms develop. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flammability Summary (OSHA):	Product is not known to be flammable, combustible, pyrophoric or explosive.
<u>Flammable Properties</u> Flash Point: Autoignition Temperature: Fire / Explosion Hazards:	No data. No data. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Extinguishing Media: Fire Fighting Instructions:	Water spray In case of fire, use normal fire-fighting equipment
Hazardous Combustion	and the personal protective equipment recommended in Section 8 to include a NIOSH approved self-contained breathing apparatus. During a fire, irritating and highly toxic gases may
Products:	be generated by thermal decomposition or combustion., Hazardous combustion/decomposition products may include but are not limited to:, Copper Fumes, Copper metal and copper oxides
Upper Flammable / Explosiv Limit, % in air:	
Lower Flammable / Explosiv Limit, % in air:	e No data.

6. ACCIDENTAL RELEASE MEASURES

Personal Protection for Emergency Situations:	No extra protection required beyond that listed in Section 8. In case of fire, use normal fire fighting equipment.
Spill Mitigation Procedures	
Air Release:	Hazardous concentrations in air may be found in local spill area and immediately downwind. Contain all solids for treatment or disposal.
Water Release:	This material is insoluble in water. Notify all downstream users of possible contamination. Contain all solids for treatment or disposal.
Land Release:	Avoid dust generation. Contain all solids for treatment or disposal.

Additional Spill Information

Remove all sources of ignition. Utilize emergency response personal protection equipment prior to the start of any response. Evacuate all non-essential personnel. Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Nonsparking tools should be used. Dispose of spill residues per guidelines under Section 13, Disposal Consideration.

7. HANDLING AND STORAGE

Handling: Storage:	DO NOT BURN TREATED WOOD. Whenever possible, sawing or machining treated or untreated wood should be performed outdoors to avoid accumulations of airborne wood dust. Wear gloves, eye protection, dust mask and protective clothing. Do not use treated chips or sawdust as mulch. Wash hands thoroughly before eating, drinking, using tobacco products, and/or using restrooms. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Minimize dust generation and accumulation. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Keep away from unguarded flame, sparks, and heat sources. Protect from physical damage. Maintain good
Incompatible Materials for	housekeeping. oxidizers strong acids and bases
Storage:	

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	wood should be to avoid accumu	performed outdoors lations of airborne we	ning treated or untreated or in well ventilated areas ood dust.Ventilation should elow the recommended
Protective Equipment	for Routine Use of	Product	
Respiratory Protection :	P95 or P100 Particula Wear a NIOSH approvapor levels exceed t approved respirator is	ate filter respirator. FOR oved P100 particulate filte	
Respirator Type :	For plywood products respirator with combi a P100 filter. Air purif	s only: A NIOSH approve nation formaldehyde/orga ying respirators should n ospheres or if exposure of	d full-face air purifying anic vapor cartridge and ot be used in oxygen
Skin Protection :	Wear leather gloves		pants, and steel-toed shoes
Eye Protection:		with side shields or chem	ical goggles when sawing or
Protective Clothing Type: General Protective Measures:	Wear leather gloves Due to the explosive should be taken wh products to prevent methods and/or exp dust. Local exhaus	s. e potential of dust when s en sawing, sanding, or m sparks or other ignition s losion suppression syste t ventilation is recommen uct. General dilution vent	suspended in air, precautions achining wood or wood ources. If required, use wet tims to reduce generation of ded when sawing, sanding, or ilation is recommended in
Exposure Limit Data			
CHEMICAL NAME	<u>CAS #</u>	Name of Limit	Exposure

CHEMICAL NAME Wood Dust	<u>CAS #</u>	<u>Name of Limit</u> ZUS_OSHAZ3	Exposure 15.0 mg/m3 PEL Total dust (as nuisance dust)
Wood Dust		ZUS_OSHAZ3	5.0 mg/m3 PEL Respirable fraction. (as nuisance dust)
Wood Dust		ZUS_ACGIH	0.5 mg/m3 TWA inhalable fraction (Western Red Cedar)
Wood Dust		ZUS_ACGIH	1.0 mg/m3 TWA inhalable fraction (All other species)
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_ACGIH	0.3 ppm C

			MATERIAL SAFETY DATA SHEET
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAPO	0.75 ppm TWA See Table Z-2 for operations or sectors excluded from section 1910.1048 or for which limit(s) is(are) stayed. Sec. 1910.1048 Formaldehyde., Sec. 1910.1048 Formaldehyde.
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAPO	2 ppm STEL See Table Z-2 for operations or sectors excluded from section 1910.1048 or for which limit(s) is(are) stayed. Sec. 1910.1048 Formaldehyde., Sec. 1910.1048 Formaldehyde.
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAP2	0.75 ppm TWA Sec. 1910.1048 Formaldehyde., see 1910.1048
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAP2	2 ppm STEL Sec. 1910.1048 Formaldehyde., see 1910.1048
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAP1	0.75 ppm TWA
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAP1	2 ppm STEL
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAP1	
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAP2	
Formaldehyde (by-product of the untreated plywood article)	50-00-0	ZUS_OSHAPO	
Formaldehyde (by-product of the untreated plywood article)	50-00-0	NIOSH-IDLH	20 ppm (Only applies to plywood products.)
BASIC COPPER CARBONATE	12069-69- 1	ZUS_OSHAP1	0.1 mg/m3 PEL (Value for copper fume.)
BASIC COPPER CARBONATE	12069-69- 1	ZUS_ACGIH	0.2 mg/m3 TWA (Value for copper fume.)
BASIC COPPER CARBONATE	12069-69- 1	NIOSH-IDLH	100 mg/m3

9. PHYSICAL AND CHEMICAL PROPERTIES

ed
е

Boiling Point:	Not applicable
	Not applicable
Freezing Point:	Not applicable
Melting Point:	No data
Density:	solid
Vapor Pressure:	Not applicable
Vapor Density:	Not applicable
Viscosity:	Not applicable
Fat Solubility:	No data
Solubility in Water:	insoluble
Partition coefficient n-	No data
octanol/water:	
Evaporation Rate:	Not applicable
Oxidizing:	The substance has no oxidizing properties
Volatiles, % by vol.:	No data
VOC Content	No data
HAP Content	No data

10. STABILITY AND REACTIVITY

Stability and Reactivity Summary:	Stable under normal conditions. Product will not undergo hazardous polymerization.
Conditions to Avoid:	Sparks, open flame, other ignition sources, and elevated temperatures., Contact with incompatible substances
Chemical Incompatibility:	strong acids, oxidizers
Hazardous Decomposition Products:	During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.
Decomposition Temperature:	No data

11. TOXICOLOGICAL INFORMATION

Component Animal	Toxicology
<u>Oral LD50 value</u> : BASIC COPPER CARBONATE	LD50 = 1,350 mg/kg rat
<u>Dermal LD50 value</u> : BASIC COPPER CARBONATE	no data available
Inhalation LC50 value: BASIC COPPER CARBONATE	no data available
Product Animal Tox	<u>kicity</u>
Oral LD50 value:	LD50 Believed to be > 5,000 mg/kg Rat
Dermal LD50 value:	LD50 Believed to be > 2,000 mg/kg Rabbit
Inhalation LC50 value:	No data
Skin Irritation:	Prolonged and/or repeated contact with treated or untreated wood dust may result
Skin Irritation: Wolmanized® µCA-C Tre	

Eye Irritation: Skin Sensitization: Subchronic / Chronic	in mild irritation. Treated or untreated wood dust may cause mechanical irritation. Various species of untreated wood dust can elicit an allergic respiratory response in sensitized persons., Various species of untreated wood dust can elicit an allergic type skin irritation in sensitized persons. May cause respiratory sensitization and/or irritation., Treated or untreated wood
Toxicity:	dust, depending on the species, may cause dermatitis on prolonged, repetitive contact.
Reproductive and Developmental Toxicity	Not known or reported to cause reproductive or developmental toxicity.
Mutagenicity:	Not known or reported to be mutagenic.
Carcinogenicity:	IARC has classified untreated hardwood and hardwood/softwood mix wood dust as a Group 1 human carcinogen. The wood dust classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures to untreated wood dust. NTP has classified all untreated wood dust as a carcinogen.

12. ECOLOGICAL INFORMATION

Overview:

No aquatic toxicity data is available for this product.

13. DISPOSAL CONSIDERATIONS

CARE MUST BE TAKEN TO PREVENT ENVIRONMENTAL CONTAMINATION FROM THE USE OF THE MATERIAL. THE USER OF THE MATERIAL HAS THE RESPONSIBILITY TO DISPOSE OF UNUSED MATERIAL, RESIDUES AND CONTAINERS IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT, STORAGE AND DISPOSAL FOR HAZARDOUS AND NONHAZARDOUS WASTES.

Waste Disposal Summary :	If this product becomes a waste, it will be a nonhazardous waste according to U.S. RCRA regulations. Dispose of in accordance with all Local, State, Federal, and Provincial Environmental Regulations.
Disposal Methods :	Dispose of in a permitted industrial waste landfill following Federal, State Local, or Provincial regulations.
Wolmanized® µCA-C Treated Wood REVISION DATE: 09/21/2009	Page 9 of 13

Potential US EPA Waste Codes : Not applicable

14. TRANSPORT INFORMATION

Land (US DOT): NOT REGULATED AS A DOT HAZARDOUS MATERIAL Water (IMDG): NOT REGULATED AS A HAZARDOUS MATERIAL,

Flash Point: No data.

Air (IATA): NOT REGULATED AS A HAZARDOUS MATERIAL, Emergency Response Guide Not applicable Number:

15. REGULATORY INFORMATION

UNITED STATES:

Toxic Substances Control Act (TSCA):	This item is exempt from TSCA and FIFRA under the treated
EPA Pesticide Registration Number:	article exemption per 40 CFR 152.25(a). None established

FIFRA Listing of Pesticide Chemicals Not registered in the US under FIFRA. (40 CFR 180):

Superfund Amendments and Reauthorization Act (SARA) Title III:

Hazard Categories Sections 311	/ 312 (40 CFR 370.2):
Health	Immediate (Acute) Health Hazard, Delayed
	(Chronic) Health Hazard
Physical	None

Emergency Planning & Community Right to Know (40 CFR 355, App. A):

Extremely Hazardous Substance Section 302 - Threshold Planning Quantity:

ZUS_SAR302 TPQ (threshold planning None established quantity)

Reportable Quantity (49 CFR 172.101, Appendix):

ZUS_CERCLA	Reportable quantity	None established
ZUS_SAR302	Reportable quantity	None established

Supplier Notification Requirements (40 CFR 372.45), 313 Reportable Components

De minimis concentration	Copper compounds (Non-carcinogenic)
	Value: 1%
	Copper Compounds
	Value: < 1% by weight
	De minimis concentration

Clean Air Act Toxic ARP Section 112r:CAA 112RNone established

Clean Air Act Socmi:HON SOCNone established

Clean Air Act VOC Section 111:CAA 111None established

Clean Air Act Haz. Air Pollutants Section 112:

CAA AP None established

State Right-to-Know Regulations Status of Ingredients

Pennsylvania:

CAS #	COMPONENT NAME
12069-69-1	BASIC COPPER CARBONATE
34590-94-8	Propanol, (2,methoxy-methylethoxy-)
7632-00-0	Sodium Nitrite

ZUSPA_RTK

Pennsylvania: Hazardous substance list 1990-01-01 COPPER COMPOUNDS Environmental hazard, hazardous substance

Pennsylvania: Hazardous substance list 1989-08-11 PROPANOL, (2-METHOXYMETHYLETHOXY)-

Pennsylvania: Hazardous substance list 1989-08-11 NITROUS ACID, SODIUM SALT Environmental hazard

New Jersey:

CAS #	COMPONENT NAME
12069-69-1	BASIC COPPER CARBONATE
34590-94-8	Propanol, (2,methoxy-methylethoxy-)

7632-00	-0
ZUSNJ	RTK

Sodium Nitrite

New Jersey Right to Know Hazardous Substance List (RTK-HSL) 1989-12-01 COPPER compounds hazardous substance

New Jersey Right to Know Hazardous Substance List (RTK-HSL) 1989-12-01 COPPER, all inorganic compounds of hazardous substance

New Jersey Right to Know Hazardous Substance List (RTK-HSL) 2007-03-01 COPPER COMPOUNDS

New Jersey Right to Know Hazardous Substance List (RTK-HSL) 2007-03-01 DIPROPYLENE GLYCOL METHYL ETHER PROPANOL, 1(or 2)-(2-METHOXYMETHYLETHOXY)- (2-METHOXYMETHYLETHOXY) PROPANOL

New Jersey Right to Know Hazardous Substance List (RTK-HSL) 2007-03-01 SODIUM NITRITE NITROUS ACID, SODIUM SALT

Massachusetts:

CAS #	COMPONENT NAME	
34590-94-8	Propanol, (2,methoxy-methylethoxy-)	
7632-00-0	Sodium Nitrite	

ZUSMA_RTK

Massachusetts Right to Know List of Chemicals and Hazard Classifications 1993-04-24 DIPROPYLENE GLYCOL METHYL ETHER

Massachusetts Right to Know List of Chemicals and Hazard Classifications 1993-04-24 SODIUM NITRITE

California Proposition 65:

CAS # COMPONENT NAME

ZUSCA_P65

None established

WHMIS Hazard Classification:

Ingredient Disclosure List (WHMIS) 2007-08-24 Threshold limits: 1 Weight % 985 Copper(II) carbonate hydroxide

Ingredient Disclosure List (WHMIS) 2007-08-24 Threshold limits: 1 Weight % 821 Dipropylene glycol methyl ether

Ingredient Disclosure List (WHMIS) 2007-08-24 Threshold limits: 1 Weight % 1218 Sodium nitrite

16. OTHER INFORMATION

MSDS REVISION STATUS :	Revised to meet the ANSI standard of 16 sections
SECTIONS REVISED:	2, 5, 6, 7, 8
Major References :	Available upon request.

THIS MATERIAL SAFETY DATA SHEET (MSDS) HAS BEEN PREPARED IN COMPLIANCE WITH THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200. THE INFORMATION IN THIS MSDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. THE MANUFACTURER BELIEVES THIS INFORMATION TO BE RELIABLE AND UP TO DATE AS OF THE DATE OF PUBLICATION BUT, MAKES NO WARRANTY THAT IT IS.