


# USG SHEETROCK® BRAND LAY-IN GYPSUM CEILING PANELS

CLIMAPLUS™ PERFORMANCE



USG Sheetrock® Brand  
Lay-In Gypsum Ceiling Panel  
with ClimaPlus™ Performance/  
USG Donn® Brand ZXL™ Acoustical  
Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- USG Clean Room™ panels have a vinyl-laminated face with sealed back and edges for use in cleanroom environments up to Class 100/ISO 5.
- Washable and scrubbable finish—impact and scratch resistant.
- USDA Certified Biobased Product.<sup>7</sup>
- Panels meet USDA/FSIS requirements for food processing areas.
- ClimaPlus™ 30 year limited system warranty against visible sag.

## APPLICATIONS

- Kitchens and food preparation areas
- Restrooms and utility areas
- Locker rooms
- Parking garages
- Exterior protected soffits

## SUBSTRATE

- Gypsum panel

Smooth-Textured Panel - Vinyl

# USG SHEETROCK® BRAND LAY-IN GYPSUM CEILING PANELS

CLIMAPLUS™ PERFORMANCE

**ORDER SAMPLES/LITERATURE**  
USG: [samplitt@usg.com](mailto:samplitt@usg.com)  
fax: 888 874-2348 | [usg.com](http://usg.com)  
CGC: contact Sales Representative

**TECHNICAL SERVICES**  
800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL**  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[cgcdesignstudio.com](http://cgcdesignstudio.com)



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL 2818

**30** YEAR LIMITED SYSTEM  
WARRANTY  
• No Visible Sag  
• Mold/Mildew Protection

**10** YEAR  
AVAILABILITY  
3270

**HRC** HIGH RECYCLED  
CONTENT



## USG SHEETROCK® BRAND LAY-IN CEILING PANEL

## USG SHEETROCK® BRAND LAY-IN CEILING PANEL CLEAN ROOM™ 5

### GRID PROFILE OPTIONS

### PHYSICAL DATA/ FOOTNOTES

UL Classified

Edge	Panel Size	Fire Rating <sup>2</sup>	Item No.	NRC <sup>4</sup>	CAC Min.	LR <sup>3</sup>	Color	Abuse Resistant	Grid Options	VOC Emissions	Recycled Content <sup>1</sup>	Panel Cost
SQ	2'x2'x1/2"		3260	–	35	0.77	White		A, B, C, D	Low	80%	\$
	2'x4'x1/2"		3270	–	40	0.77	White		A, B, C, D	Low	80%	\$
SQ	2'x4'x1/2"		3200	–	40	0.77	White		A, B, C, D	Low	80%	\$\$

#### Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on [usg.com](http://usg.com) and at [spot.ul.com](http://spot.ul.com).

#### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

#### Firecode®

Abuse Resistant

A USG DXL™	B USG DXLA™	C USG ZXLA™	D <sup>6</sup> USG CE™

**Product literature**  
Data sheet: SC1820

**ASTM E1264 classification**  
Type XX, Pattern G

**ASTM E84 and CAN/ULC S102  
surface-burning characteristics**  
Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

**UL Type**  
FC-CB

**Weight**  
1/2" = 2.00 lb./sq. ft.

**Online tools**  
[usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com)

**Thermal resistance**  
1/2" = R-0.45

**Maximum backloading**  
See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

**Maintenance**  
Can be cleaned easily with a damp sponge. Use mild detergent and water—do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

**Application considerations**  
Product is directional. Install with all manufactured edges parallel and in the same direction.

#### Notes

- For details, see USG Sustainability tool at [usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com).
- Fire-rated items: see UL design details.
- LR values are shown as averages.
- NRC rating is 0.10. USG does not consider a ceiling panel to be acoustically rated if NRC is less than 0.50.
- Field-cut edges of USG Clean Room™ panels must be sealed with white latex paint.
- Clean Room-rated applications require a suspension system with gasketed tee flanges such as USG Donn® Brand CE™.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on [biopreferred.gov](http://biopreferred.gov) website.

#### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

**SC1820/rev. 7-20**  
© 2020 USG Corporation and/or its affiliates. All rights reserved.  
Printed in USA

Manufactured by  
United States Gypsum Company  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CE, CLEAN ROOM, CLIMAPLUS, DONN, DXL, DXLA, FIRECODE, SHEETROCK, ZXLA, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

