

Material Safety Data Sheet

80831 Sto Plex W

Section I - Manufacturer's Information

Identity: Sto Plex W Common Name/Synonym: Waterbased Acrylic Coating

DOT Hazardous Class: Not Regulated Manufacturer's Sto Corp. Information #: (404) 346-3666 6175 Riverside Drive, SW Name: CAS Number: Not Registered

Emergency #: (800) 424-9300 Atlanta, GA 30331

Section II - Preparation Information

Prepared By: Sto Corp. Research and Development Department Date Prepared: 09-Jun-10

Section III - Hazardous Ingredients

Component - A			TWA/TLV				
Ingredient	Percent ww	CAS Number	OSHA	ACGIH	Other	LD50	LC50
Trimethylpentanediol Monoisobutyrate	1-5	25265-77-4	N/E mg/m³	N/E mg/m³	N/E mg/m³	3200 mg/kg	> 3.55 mg/L

Section IV - Physical/Chemical Characteristics

Component - A

Boiling Point: 100 deg C/212 deg F Vapor Pressure: N/E pH Level: 7.5 - 10.0 VaporDensity [Air=1]: N/E

Melting Point: N/A Physical State: Liquid Evaporation Rate [Ether=1]: < 1 Solubility in Water: Miscible

Specific Gravity: [H2O=1]: > 1.0 Freezing Point: 0 deg C/32 deg F Odor Threshold: N/E

Appearance and Odor: Milky Liquid - Slight Odor Coefficient of Water/Oil Distribution: N/E

Section V - Fire and Explosion Hazard Data

Component - A

Flammability: N/A Flash Point: N/A Autoignition Temperature: N/A

Limits LEL/UEL: N/E - N/E Sensitivity to impact: None Sensitivity to Static Discharge: None

Hazardous Decomposition Special Firefighting

Products: COx, NOx, Smoke, Hydrocarbons Procedures: SCBA, full protective gear

Unusual Fire and Explosive

Hazards: Material may spatter above 100 deg C/212 deg F Extinguishing Media: Water spray, foam, dry chemical

Section VI - Reactivity Data

-Component - A

Hazardous Decomposition Products: None Stability: Stable Incompatibility (Materials to Avoid): None Conditions to Avoid: None

Hazardous Polymerization: None

Section VII - Health Hazard Data

NTP· IARC: No OSHA Regulated: No LD50: N/A LC50: N/A Carcinogencity: No Nο

Effects and Hazards of

Eye Contact: Direct contact with material may cause irritation.

Effects and Hazards of

Product is waterbased. For normal application, inhalation is not expected to be a primary route of exposure. Consult Inhalation (Breathing):

Section IX - Precautions for Safe Handling and Use for further details.

Effects and Hazards of Contact with skin may cause reddening or a slight rash in individuals with sensitive skin. Skin Contact:

Effects and Hazards of

Ingestion (Swallowing):

May cause some stomach distress.

0 PPE: HMIS RATINGS Health: Flammability Reactivity:



Material Safety Data Sheet

80831 Sto Plex W

Section VIII - Emergency and First Aid Procedures

Treatment for Eye

Contact:

As with any foreign material in the eyes, they should be flushed for fifteen minutes with running water while holding the eyes open. This will assist in flushing material from the eye. If irritation continues, seek medical attention.

Treatment for Inhalation

(Breathing):

If respiratory irritation occurs, go to fresh air. Flood work area with fresh air and if irritation continues, seek medical attention.

Treatment for Skin

Contact:

Wash with mild soap and water. Hand creams should be used to prevent dry skin. If skin irritation, reddening or a rash

occur, seek medical attention.

Treatment for Ingestion

(Swallowing):

Contact medical help immediately; untrained first aid personnel should not attempt to administer first aid.

Section IX - Precautions for Safe Handling and Use

Steps to be taken in case

material is released or

spilled (Dry Stage):

Sweep and dispose of in proper receptacle.

Steps to be taken in case

material is released or

spilled (Wet Stage): Scoop into proper receptacle and allow to harden.

Waste Disposal

Method:

Per local, state and federal regulations.

Precautions To Be Taken

In Handling and Storing:

Store in a cool dry location, out of direct sunlight. Protect from freezing.

Other Precautions:

This material is an industrial product designed to be used by professionals familar with the requirements of this material

safety data sheet.

Respiratory Protection:

Respiratory protection is not required for normal use of this product. If material is ground upon or sanded when it is dry, NIOSH/MSHA approved respirators for dust should be provided and worn. All workers required to use respiratory protection

should be trained in their proper selection, use and care.

Ventilation: Recommended; local or mechanical when mixing, applying or sanding the product in the dry state.

Protective Gloves: Recommended; plastic or rubber.

Eye Protection: Recommended; chemical splash safety goggles.

Other Protective

Recommended; spalsh bib and protective clothing. Equipment:

Work and Hygienic

Practices:

Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating

California Proposition 65:

This product contains trace materials (< 0.1%) not listed in Section III which are considered carcinogens by the State of

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.