



1027 JEFFERSON AVE. UTICA, NY  
724-5970 1-800-448-3133



161 W. Main Street - Ilion, NY 13357  
315-895-7437 - Fax: 315-895-8009



## Original Blue Tapcon<sup>®</sup> Concrete Screws

With over one billion anchors sold, the Original Blue Tapcon with Climaseal<sup>®</sup> coating provides:

- Superior holding strength
- Corrosion-resistance and long-lasting performance
- The ability to withstand harsh conditions
- Long-lasting performance
- A reputation for quality, strength and ease of installation



Anchor Diameter <i>Diámetro del ancla</i>	Drill Bit <i>Broca</i>	Min. Anchor Embedment <i>empotramiento de anclaje mínimo</i>	Phillips Bit <i>Punta Phillips</i>	Nut Driver <i>Llave de tuercas</i>
3/16"	5/32"	1"	#2	1/4" Hex
1/4"	3/16"	1"	#3	5/16" Hex

### Installation Instructions

Read these instructions carefully. Failure to follow these instructions can result in serious personal injury.

**Drill** using a hammer drill, drill hole 1/4" deeper than anchor embedment. Use the charts below to select the correct drill bit.  
Clean Hole. Using a blow out bulb or compressed air, remove dust from hole.

**Drive** anchor using a hammer drill with nut driver or Phillips bit until fully seated.



### Sizes available (Phillips and Hex Head):

3/16" x 1-1/4"	3/16" x 1-3/4"	3/16" x 2-1/4"	3/16" x 2-3/4"	3/16" x 3-1/4"	3/16" x 3-3/4"
1/4" x 1-1/4"	1/4" x 1-3/4"	1/4" x 2-1/4"	1/4" x 2-3/4"	1/4" x 3-1/4"	1/4" x 3-3/4"