

**View Section :**    [1](#)   [2](#)   [3](#)   [4](#)   [5](#)   [6](#)   [7](#)   [8](#)   [9](#)   [10](#)   [11](#)   [12](#)   [13](#)   [14](#)   [15](#)   [16](#)

**SECTION 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION**

##1

**Product Name:**                    **Wood and Wood Products - (Phenolic Bonded/LFE)**  
**Manufacturer MSDS.:**            ##1  
**Distributor Name:**                BlueLinX Corporation  
**Distributor Address:**            4300 Wildwood Parkway  
    Atlanta, GA 30339-8401  
    (888) 602-BLUE (2583) MSDS Request

**CHEMTREC Numbers:**

**For emergencies in the US, call CHEMTREC: 800-424-9300**

**Revision Date:**                    09/06/2006  
    Supersedes: 05/10/2004  
**Trade Names:**                    Wood and Wood Products - (Phenolic Bonded/LFE)  
    Cellulosic Wood Fiber Insulating Board (Softboard)  
    Engineered Lumber (LVL, Glulam, Prefabricated Wood I-Joists,  
    Rim Board, etc.)  
    Hardboard (Standard, Tempered or Perforated)  
    Imported Hardwood Plywood  
    Lumber  
    Millwork  
    Moulding  
    Oriented Strand Board (OSB)  
    Softwood Plywood  
    Wood Siding

**General Use:**                      Building materials - structural, industrial or decorative  
**HMIS Hazard Scale:**  
 0 = Minimal  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe  
 \* = Chronic Health Hazard

**NFPA Hazard Scale:**  
 0 = Minimal  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Product Codes:**

**NFPA**

1      1  
1      0

**HMIS**

<b>HEALTH</b>	1
<b>FIRE</b>	1
<b>REACTIVITY</b>	0
<b>PPE</b>	

[To Top of page](#)

**SECTION 2 : COMPOSITION, INFORMATION ON INGREDIENTS**

##1

<b>Ingredient Name</b>	<b>CAS#</b>	<b>Ingredient Percent</b>
Wood	Mixture	90-100%
<b>EC Index Number:</b>	1 See Section 8 for exposure limits for wood dust generated from sawing, sanding or machining the product.  Some hardwood lumber is dipped with an insecticide, pesticide and/or sap stain control. The lumber is then air or kiln dried. No chemical residue is left on the surface of the board. Some wood products contain cured binders and other non-hazardous ingredients.	

[To Top of page](#)

---

## SECTION 3 : HAZARDS IDENTIFICATION


##1

<b>Emergency Overview:</b>	CAUTION! Sawing, sanding or machining wood products may produce wood dust, which cause a fire and explosion hazard. Wood dust may cause irritation to the eyes, skin and respiratory tract. Prolonged overexposure to wood dust may cause nasal cancer. Repeated exposure to certain types of wood dust (such as western red cedar) may cause allergic skin and respiratory reaction (sensitization).
<b>Physical State:</b>	Description: Solid wood, such as lumber, and wood products, such as softwood plywood, not bound with a urea-formaldehyde resin.
<b>HMS Ratings:</b>	Health: 1* Fire: 1 Reactivity: 0  Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic Health Hazard

### Wood :

#### Potential Health Effects:

<b>Eye Contact:</b>	Wood dust can cause mechanical irritation.
<b>Skin Contact:</b>	Some species of wood dust may evoke allergic contact dermatitis in sensitized individuals. If an allergy pre-exists or develops, it may be necessary to remove the sensitized worker from further exposure to wood dust or wood-based products.
<b>Inhalation:</b>	Wood dust may cause nasal dryness, irritation, coughing and sinusitis. Repeated exposures to certain types of wood dust (such as western red cedar) can produce allergic responses in some individuals. If an allergy pre-exists or develops, it may be necessary to remove the sensitized worker from further exposure to wood dust or wood-based products. Prolonged overexposure to wood dust is associated with an increased risk of cancer of the nasal cavity.
<b>Ingestion:</b>	Not applicable under normal conditions of use.
<b>Target Organs:</b>	Eye, Skin and Respiratory Tract.
<b>Aggravation of Pre-Existing Conditions:</b>	Wood dust exposure may aggravate pre-existing skin, eye, respiratory and cardiovascular disorders.

[To Top of page](#) 

---

## SECTION 4 : FIRST AID MEASURES

##1

<b>Eye Contact:</b>	Immediately rinse with water. Remove contact lenses. Hold eyelids apart and flush eyes thoroughly with water. If irritation persists or for foreign body in the eye, seek medical attention.
<b>Skin Contact:</b>	Wash affected areas with soap and water until dust is entirely removed from skin. Immediately remove contaminated clothing. If rash, dermatitis or irritation develops, seek medical attention. Launder contaminated clothing before reuse or dispose of properly.
<b>Inhalation:</b>	Remove to fresh air immediately. If breathing is difficult, trained personnel should administer oxygen. If breathing has ceased apply artificial resuscitation using oxygen and a suitable mechanical device such as a bag and a mask. Get immediate medical attention.
<b>Ingestion:</b>	Not applicable under normal conditions of use.

[To Top of page](#) 

---

## SECTION 5 : FIRE FIGHTING MEASURES

##1

<b>Explosion:</b>	Explosive Limits: Sawing, sanding or machining wood products can produce wood dust as a by-product. Wood dust is a strong to severe explosion hazard if a dust "cloud" contacts an ignition source. 212 deg F (100 deg C) has been suggested as the upper temperature limit for continuous exposure for wood without risk of ignition (wood dust may require a still lower temperature). An airborne concentration of 40 grams of dust per cubic meter of air is often used as the lowest explosion limit (LEL) for wood dust.
<b>Flash Point:</b>	Not applicable.
<b>Auto Ignition Temperature:</b>	400 deg - 500 deg F (204 deg - 260 deg C)

**Extinguishing Media:** Fire: Water, dry chemical and other agents rated for a Type A fire.  
**Hazardous Combustion Byproducts:** Thermal-oxidative degradation, or burning, of wood can produce irritating and potentially toxic fumes and gases including carbon monoxide, aldehydes and organic acids.  
**Fire Fighting Instructions:** Use water to wet down wood dust to reduce the likelihood of ignition or dispersion of dust into the air. Remove burned, charred or wet dust to open, secure area after fire is extinguished.

#### NFPA

**Health:** 1

**Flammability:** 1

**Reactivity:** 0

**Other:**

**NFPA Hazard Scale:** 0 = Minimal  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe

[To Top of page](#) 

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

##1

**Personal Precautions:** Wear appropriate protective clothing and equipment of indicated in Section 8. Do not inhale dusts during clean-up. Avoid eye contact or repeated or prolonged contact with skin.

**Spill Cleanup Measures:** Wood dust may be vacuumed or shoveled for recovery or disposal. Wet down accumulated dusts prior to vacuuming or shoveling in order to prevent explosion hazards. Eliminate all ignition sources. Avoid dusty conditions and provide good ventilation. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize creation of airborne dust.

[To Top of page](#) 


---

## SECTION 7 : HANDLING and STORAGE

##1

**Handling:** Avoid repeated or prolonged breathing of wood dust. Avoid eye contact or repeated or prolonged contact with skin. Change protective clothing and gloves when sign of contamination appear. Water spray may be used to wet down wood dust generated by sawing, sanding or machining to reduce the likelihood of ignition or dispersion of dust into the air.

**Storage:** Wood products are combustible and, therefore, should not be subjected to temperatures exceeding the autoignition temperature.

[To Top of page](#) 

---

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION

##1

**Engineering Controls:** Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sanding, sawing or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended. Provide local exhaust as necessary to maintain exposure levels below the occupational exposure limits.

**Personal Protective Equipment Routine Handling:** (GENERAL PPE RECOMMENDED BELOW: IT MAY BE NECESSARY TO FOLLOW SPECIFIC PPE REQUIREMENTS AS DETERMINED BY YOUR WORKPLACE)

**Skin Protection Description:** Protective equipment such as gloves and outer garments may be needed to reduce skin contact. After working with wood and before eating, drinking, toileting and use of tobacco products, wash exposed areas thoroughly with soap and water.

**Eye/Face Protection:** Safety goggles or safety glasses recommended as conditions indicate when sawing, sanding or machining wood products.

**Protective Clothing/Body Protection:** No special requirements under normal conditions of use. Protective clothing should be worn where prolonged skin contact may occur. Protective clothing should be laundered separately from household clothing and before reuse.

**Respiratory Protection:** Use NIOSH/OSHA approved respirator when ventilation is not possible and if occupational exposure limits for wood dust may be exceeded.

**Exposure Limits:** Wood Species: Western Red Cedar  
CAS NO.: Mixture  
OSHA PEL: 5 mg/m<sup>3</sup> TWA (respirable dust); 15 mg/m<sup>3</sup> STEL (total dust) as Particulates not Otherwise Classified

ACGIH TLV: 0.5 mg/m3 TWA (inhalable fraction) sensitizer

Wood Species: Wood Dusts, all other species

CAS NO.: None

OSHA PEL: 5 mg/m3 TWA (respirable dust); 15 mg/m3 STEL (total dust) as Particulates not Otherwise Classified

ACGIH TLV: 1 mg/m3 TWA (inhalable fraction)

[To Top of page](#) 

---

## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

##1

---

Physical State/Appearance:	Varies
Odor:	Wood species dependent
Physical State:	Solid
pH:	Not applicable
Vapor Pressure:	Not applicable
Vapor Density:	Not applicable
Boiling Point:	Not applicable
Melting Point:	Not applicable
Solubility:	(H2O): Insoluble
Specific Gravity:	< 1.0

[To Top of page](#) 

---

## SECTION 10 : STABILITY and REACTIVITY

##1

---

Chemical Stability:	This is a stable material.
Conditions to Avoid:	Wood dust generated from sawing, sanding or machining the product is extremely combustible. Keep in cool dry place away from ignition sources.
Incompatibilities with Other Materials:	Oxidizing agents and drying oils.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Hazardous Combustion Products: Thermal-oxidative degradation or burning, of wood can produce irritating and potentially toxic fumes and gases including carbon monoxide, aldehydes and organic acids.

[To Top of page](#) 

---

## SECTION 11 : TOXICOLOGICAL INFORMATION

##1

### Wood :

---

Carcinogenicity:	WOOD DUST: The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) classify wood dust as a (known) human carcinogen (Group I).
Other Toxicological Information:	WOOD DUST: Wood dust generated from sawing, sanding or machining this product may cause nasal dryness, irritation, coughing and sinusitis. This classification is based primarily on increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust.

[To Top of page](#) 

---

## SECTION 12 : ECOLOGICAL INFORMATION

##1

---

Ecological Paragraph:	General Product Information: This product is not expected to have ecological effects on the environment.
Environmental Fate:	No information available.
Effect of Material On Aquatic Life:	Component Analysis - Ecotoxicity - Aquatic Toxicity: Aquatic values were not found for the individual components listed in Section 3.

[To Top of page](#) 

---

## SECTION 13 : DISPOSAL CONSIDERATIONS


---

##1

**Waste Disposal:** In its purchased form, dispose of Wood and Wood Products by ordinary trash collection. Sawdust and construction debris should be cleaned up and disposed of after construction. Incinerate or landfill in accordance with local, state and federal regulations.

**EPA Waste Number:** General Product Information:  
If the material is altered by processing, use or contamination, the waste must be tested using methods described in 40 CFR 261 to determine if it meets applicable definitions of hazardous wastes.

Component Waste Numbers:  
No EPA Wastes Numbers are applicable for this product's components.

[To Top of page](#) 

---


## SECTION 14 : TRANSPORT INFORMATION

---

##1

**DOT Shipping Information:** This material is not a DOT hazardous material.

**Canadian TDG:** This product is not listed as a hazardous material

[To Top of page](#) 

---

## SECTION 15 : REGULATORY INFORMATION

---

##1


**Wood :**

**TSCA 8(b): Inventory Status:** This product complies with TSCA inventory requirements.

**SARA:** Component Analysis:  
This product in its purchased form does not contain SARA identified chemicals.

**OSHA 29 CFR 1200:** General Product Information:  
Wood products are not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, wood dust generated by sawing, sanding or machining these products are hazardous.

**Canada WHMIS:** This product is not a controlled product in the purchased form. Wood dust is classified as Class D-2-A.

[To Top of page](#) 

---

## SECTION 16 : ADDITIONAL INFORMATION

---

##1

**HMIS:**

**Health Hazard:** 1\* = Slight (\* = Chronic Health Hazard)

**Fire Hazard:** 1 = Slight

**Reactivity:** 0 = Minimal

**NFPA:**

**Health:** 1 = Slight

**Fire Hazard:** 1 = Slight

**Reactivity:** 0 = Minimal

**Label Text:** Wood Products

**Label Hazard Warning:** CAUTION!

WOOD DUST CAN CAUSE A FLAMMABLE OR EXPLOSION HAZARD

WOOD DUST MAY CAUSE LUNG, UPPER RESPIRATORY TRACT, EYE AND SKIN IRRITATION. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) AND THE NATIONAL TOXICOLOGY PROGRAM (NTP) LIST WOOD DUST AS A (GROUP 1) CARCINOGEN.

**Label Precautions:** Avoid dust contact with ignition source.  
Wood dust clean up and disposal activities should be accomplished in a manner to minimize creation of airborne dust.  
Avoid breathing dust.  
Avoid dust contact with eyes and skin.

**HANDLING AND STORAGE:**  
Avoid frequently or prolonged inhalation of wood dust. Protect eyes from flying particles. Avoid contact with skin and wash exposed areas thoroughly. Change protective clothing and gloves when sign of contamination appear.

Wood products are combustible and, therefore, should not be subjected to temperatures exceeding the autoignition temperature. Water spray may be used

to wet down wood dust generated by sawing, sanding or machining to reduce likelihood of ignition or dispersion of dust into the air.

**Label First Aid:**

If inhaled, remove to fresh air. In case of contact, flush eyes and skin with water. If irritation persists, seek medical attention.

**MSDS Revision Date:**

09/06/2006  
Supercedes: 05/10/2004

**Disclaimer:**

IMPORTANT: The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations. BLUELINX CORPORATION MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. BlueLinx Corporation will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.

This Material Safety Data Sheet is being furnished for similar wood products produced by different manufacturers. Consult labels, stamps and markings on the product or packaging for the exact identity of the manufacturer.

**HMIS Hazard Scale:**

- 0 = Minimal
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe
- \* = Chronic Health Hazard

**NFPA Hazard Scale:**

- 0 = Minimal
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Key/Legend:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- C: Ceiling Limit
- CAS: Chemical Abstract Services Number
- CFR: Code of Federal Regulations
- DOT: Department of Transportation
- DSL: Domestic Substance List
- EPA: Environmental Protection Agency
- HEPA: High Efficiency Particulate Air
- HMIS: Hazardous Material Identification System
- IARC: International Agency for Research on Cancer
- NA: Not Available or Not Applicable
- NFPA: National Fire Protection Association
- NIOSH: National Institute for Occupational Safety and Health
- NJTSR: New Jersey Trade Secret Registry
- NSL: Non-Domestic Substance List
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PPE: Personal Protective Equipment
- STEL: Short Term Exposure Limit
- TLV: Threshold Limit Value
- TSCA: Toxic Substance Control Act
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Information System

For additional information, see the BlueLinx Corporation Material Safety Data Sheet for this product.

Product Services  
BlueLinx Corporation  
4300 Wildwood Parkway  
Atlanta GA 30339-8401