

Material Name: Formaldehyde-free Fiber Glass Building and Flexible Duct Insulation Safety Data Sheet

ID: 1071

Section 1 - Product and Company Identification		
Hazard Label WARNING label		
Company Information		
Johns Manville	Telephone: 303-978-2000 8:00AM-5:00PM M-F	
Insulation Systems	Internet Address: http://www.jm.com	
P.O. Box 5108	Emergency: 800-424-9300 (Chemtrec, In English)	
Denver, CO 80127 USA		
Trade Names:		
Basement Wall Insulation®, Unfaced	MR™-Faced	
ComfortTherm®	Microlite® "L"	
EasyFit®	Manufactured Housing Insulation	
Flex-Glas® PC	Multi-Purpose Fiber Glass	
Flex-Glas® EQ	Rich-R [®] Blowing Wool	
Foil-Faced Batts	Sound Control Batts	
High-Density Blowing Wool	Sound-SHIELD®	
High-Lo Temp [®] Fiber Glass Insulation Inserts	Unfaced Thermal and Acoustical Fiber Glass Insulation	
Kraft-Faced Fiber Glass Insulation	Condensation Blanket, Unfaced	

Use: For use in commercial, residential, manufactured housing, and metal buildings.

Section 2 - Hazards Identification

Emergency Overview

Inhalation of excessive amounts of dust from the product may cause temporary upper respiratory irritation and/or congestion-remove individual to fresh air.

Inhalation

Irritation of the upper respiratory tract (scratchy throat), coughing, and congestion may occur in extreme exposures.

Skin

Temporary irritation (itching) or redness may occur.

Ingestion

This product is not intended to be ingested (eaten). If ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.

Eyes

Temporary irritation (itching) or redness may occur.

Ears

Temporary irritation (itching) or redness may occur.

Primary Routes of Entry (Exposure)

Inhalation, skin, and eye contact.

Target Organs

Nose (nasal passages), throat, lungs, skin, eyes

Medical Conditions Aggravated by Exposure

Pre-existing chronic respiratory, skin, or eye diseases or conditions.

Section 3 - Composition/Information on Ingredients

CAS #	Component	Percent
Not Applicable	Fiber glass wool	80-98
Not Available	ailable Thermoset resin 2-15	
Not AvailableFoil/kraft, kraft, polyethylene facings0-15		0-15

General Product Description

Fibrous glass board, batt, blanket, or loose-fill insulation with or without tan kraft, blue kraft, or other facings. No significant odor.

Section 4 - First Aid Measures

First Aid: Inhalation

If dust is inhaled in excess of exposure limits referenced in section 8 of this safety data sheet, remove individual to fresh air. Drink water to clear throat, and blow nose to remove dust. A saline spray in the nose may help clear any fibers.

First Aid: Skin

Wash gently with soap and water to remove dust and fibers. Alternatively, fibers can be removed from the skin by use of ordinary masking or wrapping tape. Should irritation persist, seek medical attention.

First Aid: Ingestion

Rinse mouth with water to remove dust and fibers and drink plenty of water to help reduce irritation. If irritation persists, seek medical attention.

First Aid: Eyes

Do not rub or scratch eyes. Dust particles may cause the eye to be scratched. Flush eyes with large amounts of water until irritation subsides. If irritation persists, seek medical attention.

First Aid: Ears

Wash exposed skin with soap and water. If irritation develops in the inner ear, seek medical attention.

First Aid: Notes to Physician

Dust from the product may cause mechanical irritation of the eyes, skin, and upper respiratory tract. Treat symptomatically.

Method Used: Not applicable

Lower Flammable Limit (LFL): Not applicable

Flammability Classification: Not determined

Section 5 - Fire Fighting Measures

Flash Point: Not applicable

Upper Flammable Limit (UFL): Not applicable Auto Ignition: Not determined

Rate of Burning: Not determined

General Fire Hazards

There is no potential for spontaneous fire or explosion. Inorganic glass fibers are naturally non-combustible and non-flammable.

Extinguishing Media

Carbon dioxide (CO₂), water, water fog, dry chemical.

Fire Fighting Equipment/Instructions

No special procedures are expected to be necessary for this product. Normal firefighting procedures should be followed to avoid inhalation of smoke and gases.

Section 6 - Accidental Release Measures

Clean-Up Procedures

Pick up large pieces. Vacuum dusts. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation. These procedures will help to minimize potential exposures.

Section 7 - Handling and Storage

Handling Procedures

Use protective equipment as described in Section 8 of this safety data sheet when handling uncontained material. Handle in accordance with good industrial hygiene and safety practices.

Storage Procedures

Warehouse storage should be in accordance with package directions, if any. Material should be kept clean, dry, and in original packaging.

Section 8 - Exposure Controls / Personal Protection

The Occupational Safety and Health Administration (OSHA) has not adopted specific occupational exposure standards for fiber glass. Fiber glass is treated as a nuisance dust and is regulated by OSHA as a particulate not otherwise regulated (total dust) shown in CFR 1910.1000 Table Z-3. Respirable fraction 5 mg/m3 Total dust 15 mg/m3

JM has adopted the fiber glass industry voluntary Product Stewardship Program (PSP), formerly the NAIMA-OSHA Health and Safety Partnership Program (HSPP). Under the PSP, JM recommends that exposures be limited to the voluntary concentration of 1 f/cc TWA for fibers longer than 5 microns with a diameter less than 3 microns. This will help minimize potential irritation effects. The PSP also includes the PPE recommendations described below.

Material Name: Fiber Glass Building and Flexible Duct Insulation Formaldehyde-free, Antimony trioxide-free

Safety Data Sheet ID: 1071

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Safety glasses with side shields are recommended to keep dust out of the eyes.

Personal Protective Equipment: Ears

Use ear protection (earplugs, hood, or earmuffs) to prevent airborne dust or fibers from entering the ear, if necessary.

Personal Protective Equipment: Skin

Leather or cotton gloves should be worn to protect against mechanical abrasion. See also Personal Protective Equipment: General, below.

Personal Protective Equipment: Respiratory

A NIOSH-approved respirator should be used if ventilation is unavailable, or is inadequate for keeping dust and fiber levels below the applicable exposure limits referenced in Section 8 of this SDS.

Ventilation

In fixed manufacturing settings, local exhaust ventilation should be provided at areas of cutting, milling or other processing to remove airborne dust and fibers.

Personal Protective Equipment: General

Wear a cap, a loose-fitting, long-sleeved shirt and long pants to protect skin from irritation. Exposed skin areas should be washed with soap and water after handling or working with fiber glass. Clothing should be washed separately from other clothes, and the washer should be rinsed thoroughly (run empty for a complete wash cycle). This will reduce the chances of fiber glass being transferred to other clothing.

Section 9 - Physical & Chemical Properties

Appearance:	Fibrous glass board, batt, blanket, or loose
	fiber, with or without various facings
Physical State:	Solid
Vapor Pressure:	Not applicable
Boiling Point:	Not applicable
Solubility (H ₂ O):	Nil
Freezing Point:	Not applicable
Percent Volatile:	0

Odor: No significant odor

pH:	Not applicable
Vapor Density:	Not applicable
Melting Point:	>704°C/1300°F
Specific Gravity:	Variable
Evaporation Rate:	Not applicable
VOC:	Not determined

Section 10 - Stability & Reactivity Information

Stability

These products are not reactive.

Hazardous Decomposition

May form carbon dioxide and carbon monoxide.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

Acute Toxicity

A: General Product Information

Dust from this product is a mechanical irritant, which means that it may cause temporary irritation or scratchiness of the throat, and/or itching of the eyes and skin.

B: Component Analysis - LD50/LC50

No LD50/LC50's are available for this product's components.

Material Name: Fiber Glass Building and Flexible Duct Insulation Formaldehyde-free, Antimony trioxide-free

Component Carcinogenicity

Fiber glass wool

NTP: Not listed.

IARC: Group 3 - Not Classifiable (IARC Monograph 81 [2002] (listed under Man-made mineral fibres), Monograph 43 [1988])

Chronic Toxicity

Fiber Glass Wool (non-durable glass fibers):

In October 2001, IARC classified fiber glass wool as Group 3, "not classifiable as to its carcinogenicity to humans." The 2001 decision was based on current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease

In 2011, the National Toxicology Program (NTP, a component of the United States Department of Health and Human Services) issued its *12th Report on Carcinogens* (Report). The Report makes clear that any glass fibers that have been successfully assessed in an animal study and shown no cancer hazard are NOT among those "certain" fibers and NOT listed in the Report.

The glass fibers comprising the products on this MSDS have either been successfully assessed by appropriate animal protocols and / or have modeled Kdis values such that they are considered non-durable and the current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease is applicable to these fibers.

Section 12 - Ecological Information

Ecotoxicity

A: General Product Information

No data available for this product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

No ecotoxicity data are available for this product's components.

Section 13 - Disposal Considerations

US EPA Waste Number & Descriptions

A: General Product Information

This product is not expected to be a hazardous waste when it is disposed of according to the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Product characterization after use is recommended to ensure proper disposal under federal and/or state requirements.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transport Information

International Transport Regulations

These products are not classified as dangerous goods according to international transport regulations.

Section 15 - Regulatory Information

US Federal Regulations

A: General Product Information

SARA 311/312: This product is not classified as hazardous under SARA 311/312.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

The glass fibers in this product are not known to be regulated.

Other state regulations may apply. Check individual state requirements.

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer.

Co	omponent	CAS #
Fi	per glass wool	Not Applicable
L	5	

Material Name: Fiber Glass Building and Flexible Duct Insulation Formaldehyde-free, Antimony trioxide-free

Safety Data Sheet ID: 1071

TSCA Status

This product and its components are listed on the TSCA 8(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

International Regulations

A: General Product Information

These products are considered articles under both U.S. and international product regulations and as such, these products do not require registration or notification on the various country-specific inventories.

B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian H	azardous Products	Act Ingredient Disclosure List:
Component	CAS #	Minimum Concentration
Fiber glass wool	Not Applicable	1 % (related to Fibrous glass)

WHMIS Classification

Controlled Product Classification: D2A This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations. This SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Other Information

Prepared for: Johns Manville Insulation Systems P. O. Box 5108 Denver, CO USA 80217-5108

Prepared by: Johns Manville Technical Center P.O. Box 625005 Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Date	MSDS #	Reason
03/22/05	1071-1.0000	New MSDS for antimony free BI products.
06/06/05	1071-1.0001	Addition of Unfaced Sound Control Batts to Sect. 1 trade names.
06/29/06	1071-1.0002	Removed Insul-SHIELD® Unfaced Boards, Formaldehyde-free
		from trade names.
07/16/07	1071-1.0003	Regulatory update. Minor edits.
02/29/08	1071-1.0004	Removed Spin-Glas®; Steel Frame Formaldehyde-free Thermal
		and Acoustical Fiber Glass Insulation from trade names. Added
		'Antimony Trioxide-free' to material name. Edited WHMIS
		classification to D2A for fiber glass wool.
03/03/09	1071-1.0005	Addition of Pour and Rake Attic Insulation to trade names.
06/02/09 12/19/12 01/03/13 04/03/13	1071-1.0006 1071-1.0007 1071-1.0008 1071-1.0008	Addition of FlexGlas PC to trade names. Update Trade Names and regulatory information in Sec. 11. Update Trade Names. Added Flex-Glas® EQ to trade names.

Material Name: Fiber Glass Building and Flexible Duct Insulation Formaldehyde-free, Antimony trioxide-free

Safety Data Sheet ID: 1071

End of Sheet 1071