# **SAFETY DATA SHEET**

4100

# Section 1. Identification

Product name	: Medallion® Paint & Primer Satin Exterior White
Product code	: 4100
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	f the substance or mixture and uses advised against
Paint or paint related materia	al.
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300
Product Information	: 1-877-825-7727

Telephone Number	
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency Telephone Number	: (800) 424-9300

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 2.4% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 2.4% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 2.4%
GHS label elements	
Hazard pictograms	
0 malana d	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.
Response	: IF exposed or concerned: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

	Date of issue/Date	e of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version	: 7.04	1/12
4100 Medallion® Paint & Primer Satin Exterior			SHW-85	-NA-GHS-US	i.			
		White						

# Section 2. Hazards identification

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.
Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7
Zinc Oxide	≤3	1314-13-2
Benzophenone	≤0.3	119-61-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessar	<u>y first aid measures</u>
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

Potential acute health effects			
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		

Date of issue/Date	of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version :	7.04 2/12
4100	Medallion® Paint & F White	Primer Satin Exte	rior		SHW-85-NA	A-GHS-US

### Section 4. First aid measures

Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/symp	<u>otoms</u>			
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	No specific data.			
Ingestion	: No specific data.			
Indication of immediate me	dical attention and special treatment needed, if necessary			
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.			
Specific treatments	No specific treatment.			
Protection of first-aiders	<ul> <li>No action shall be taken involving any personal risk or without suitable training.</li> <li>be dangerous to the person providing aid to give mouth-to-mouth resuscitation.</li> </ul>			

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

•	
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date	of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version	: 7.04	3/12
4100	Medallion® Paint & Prin White	ner Satin Exterio	or		SHW-85-	NA-GHS-US	

### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

### Occupational exposure limits (OSHA United States)

Ingredient na	me		Exposure limits					
Titanium Dioxi	Titanium Dioxide				ACGIH TLV (United States, 3/2018). TWA: 10 mg/m <sup>3</sup> 8 hours. OSHA PEL (United States, 5/2018).			
Zinc Oxide				NIOSH REL (Ur CEIL: 15 mg/m TWA: 5 mg/m <sup>3</sup> fumes	n <sup>3</sup> 8 hours. Form: Total du nited States, 10/2016). n <sup>3</sup> Form: Dust <sup>3</sup> 10 hours. Form: Dust an n <sup>3</sup> 15 minutes. Form: Fun	nd		
				OSHA PEL (Ŭn TWA: 5 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> fraction TWA: 15 mg/m	ited States, 5/2018). <sup>3</sup> 8 hours. Form: Fume <sup>3</sup> 8 hours. Form: Respirab n <sup>3</sup> 8 hours. Form: Total du nited States, 3/2018).	ble		
Date of issue/Date of		: 5/24/2019	Date of previous issue	: 4/4/2019	Version : 7.04	4/12		
	Medallion® Paint & P White	rimer Satin Exter	IOr		SHW-85-NA-GHS-US			

# Section 8. Exposure controls/personal protection

	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Respirable fraction AIHA WEEL (United States, 7/2018).
Benzophenone	TWA: 0.5 mg/m <sup>3</sup> 8 hours.

### Occupational exposure limits (Canada)

Ingredient name	Exposure limits
Titanium dioxide	CA British Columbia Provincial (Canada, 7/2018). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Respirable dust TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Total dust CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m <sup>3</sup> 8 hours. Form: Total dus CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m <sup>3</sup> 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 10 mg/m <sup>3</sup> 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m <sup>3</sup> 15 minutes. TWA: 10 mg/m <sup>3</sup> 8 hours.
Zinc Oxide	<ul> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>15 min OEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Respirable</li> <li>CA British Columbia Provincial (Canada, 7/2018).</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Respirable</li> <li>CA Ontario Provincial (Canada, 1/2018).</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction.</li> <li>STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Respirable fraction.</li> <li>CA Quebec Provincial (Canada, 1/2014).</li> <li>TWAEV: 5 mg/m<sup>3</sup> 8 hours. Form: fume STEV: 10 mg/m<sup>3</sup> 15 minutes. Form: fume</li> <li>STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: fume</li> <li>TWAEV: 5 mg/m<sup>3</sup> 8 hours. Form: fume</li> <li>TWAEV: 2 mg/m<sup>3</sup> 8 hours. Form: fume</li> <li>STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: fume</li> <li>CA Saskatchewan Provincial (Canada, 7/2014).</li> <li>STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: fume</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: respirable dust and fume</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable</li> <li>dust and fume</li> </ul>

#### **Occupational exposure limits (Mexico)**

Ingredient name	Exposure limits
Zinc Oxide	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Respirable fraction

5/12

Date of issue/Date	of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version	:7.04
4100	Medallion® Paint & Prir White	ner Satin Exteri	or		SHW-85-	NA-GHS-US

# Section 8. Exposure controls/personal protection

Coolion of Exposed	
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	<sup>3</sup> This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Section 9 Physics	I and chemical properties

### Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point/boiling range	: 100°C (212°F)
Flash point	: Closed cup: 96°C (204.8°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.

Date of issue/Date	of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version : 7.04	6/12
4100	Medallion® Paint & Pr White	imer Satin Exte	rior		SHW-85-NA-GHS-US	

## Section 9. Physical and chemical properties

Vapor pressure	: 2.3 kPa (17.5 mm Hg) [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 1.26
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.205 cm <sup>2</sup> /s (>20.5 cSt)
Molecular weight	: Not applicable.
Aerosol product	
Heat of combustion	: 1.048 kJ/g

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzophenone	LD50 Dermal LD50 Oral		3535 mg/kg >10 g/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
Zinc Oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

## Section 11. Toxicological information

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-
Benzophenone	-	2B	-

#### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Benzophenone	Category 3		Respiratory tract irritation and Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Benzophenone	Category 2	Not determined	Not determined

### **Aspiration hazard**

Not available.

### Information on the likely : Not available.

### routes of exposure

Potential acute health effects	
Eye contact :	No known significant effects or critical hazards.
Inhalation :	No known significant effects or critical hazards.
Skin contact :	No known significant effects or critical hazards.
Ingestion :	No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate eff	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ffects
Not available.	
General	: No known significant effects or critical hazards.

Date of issue/Date of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version	:7.04	8/12
4100 Medallion White	Paint & Primer Satin Extension	erior		SHW-85-1	NA-GHS-US	

# Section 11. Toxicological information

Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

# Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure		
Titanium Dioxide Zinc Oxide	Acute LC50 >1000000 μg/l Marine water Acute IC50 1.85 mg/l Marine water Acute IC50 46 μg/l Fresh water	Fish - Fundulus heteroclitus Algae - Skeletonema costatum Algae - Pseudokirchneriella subcapitata - Exponential growth phase	96 hours 96 hours 72 hours		
	Acute LC50 98 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours		
Benzophenone	Acute LC50 1.1 ppm Fresh water Acute LC50 10.89 mg/l Fresh water	Fish - Oncorhynchus mykiss Fish - Pimephales promelas - Larvae	96 hours 96 hours		
	Chronic NOEC 1.03 mg/l Fresh water	Fish - Pimephales promelas - Embryo	32 days		

### Persistence and degradability

Not available.

Tantali

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Zinc Oxide	-	60960	high
Benzophenone	-	12.02	low

#### Mobility in soil

Soil/water partition: Not available.coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

: This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

l	Date of issue/Date	of revision	: 5/24/2019	Date of previous issue	: 4/4/2019
	4100	Medallion® Paint & Pri White	mer Satin Exteri	or	

### Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	UN3082	UN3082
UN proper shipping name	-	-	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Oxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Oxide, Nonylphenoxypoly (ethoxy)ethanol). Marine pollutant (Zinc Oxide, Nonylphenoxypoly (ethoxy)ethanol)
Transport hazard class(es)	-	-	-	9 ••••••••••••••••••••••••••••••••••••	9
Packing group	-	-	-	111	111
Environmental hazards	No.	No.	No.	Yes.	Yes.
Additional information	-	-	-	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0. 2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1. 1, 4.1.1.2 and 4.1. 1.4 to 4.1.1.8. <u>Emergency</u> <u>schedules</u> F-A, S-F

### Section 14. Transport information

Special precautions for user	consider container sizes. The mode of transport (sea, air, suitably for that mode of transport prior to shipment, and compositive responsibility of the person of unloading dangerous goods	otions are provided for informational purposes and do not e presence of a shipping description for a particular etc.), does not indicate that the product is packaged hsport. All packaging must be reviewed for suitability liance with the applicable regulations is the sole offering the product for transport. People loading and must be trained on all of the risks deriving from the hs in case of emergency situations.
Transport in bulk according : to Annex II of MARPOL and the IBC Code	Not available.	
	Proper shipping name	: Not available.
	Ship type	: Not available.

### Section 15. Regulatory information

U.S. Federal regulations : TSCA 5(a)2 proposed significant new use rules: 5-Chloro-2-methylisothiazolinone

**TSCA 5(a)2 final significant new use rules**: Trichloroethylene

: Not available.

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

**Pollution category** 

### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

International lists	<ul> <li>Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined. Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. Malaysia Inventory (EHS Register): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined.</li> </ul>
	Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Date of issue/Date	of revision	: 5/24/2019	Date of previous issue	: 4/4/2019	Version	<b>:</b> 7.04	11/12
4100	Medallion® Paint & Prin White	ner Satin Exteri	or		SHW-85-	NA-GHS-US	

### Section 16. Other information

	<b>Procedure</b>	used to	<u>o derive</u>	the	<b>classification</b>
--	------------------	---------	-----------------	-----	-----------------------

	Classification	Justification		
CARCINOGENICITY - Cat	egory 2	Calculation method		
<u>History</u>		ł		
Date of printing	: 5/24/2019			
Date of issue/Date of revision	: 5/24/2019			
Pate of previous issue : 4/4/2019				
Version	: 7.04			
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classifica IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition MARPOL = International Convention for the Prev as modified by the Protocol of 1978. ("Marpol" = 1 UN = United Nations	on Goods rtition coefficient Prevention of Pollution From Ships, 1973		

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.