



### GENERAL DESCRIPTION

This durable wall enamel protects with a 100% acrylic coating for long lasting interior beauty. The eggshell finish provides a low sheen that resists stains and fingerprints. Dries quickly and cleans up easily with soap and water.

### PRODUCT FEATURES

- 100% acrylic durability
- Stain resistant
- Washable
- Paint and primer in one product
- Mildew-resistant finish
- Dries quickly
- Soap and water cleanup

### RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

Quart – 4 per carton  
Gallon – 4 per carton  
5 gallon pail

**Case Weight:** 12.5–47 lbs.

### COMPOSITION

#### **Base and Fill Levels**

(oz./gal.)

<b>White</b>	128
<b>Pastel Base (4408)</b>	126
<b>Tint Base (4402)</b>	124
<b>Clear Base (4405)</b>	116

### APPLICATION AND CLEANUP

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage. Clean up with warm, soapy water.

#### **Airless Spray:**

**Pressure:** 2000 PSI

**Tip:** 0.017–0.019"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8" nap

### SYSTEM

### RECOMMENDATIONS

#### **Plaster:**

Prime with Medallion Interior Latex Eggshell Paint  
1–2 Coats: Medallion Interior Latex Eggshell Paint

#### **Wood:**

Prime with Medallion Interior Latex Eggshell Paint  
1–2 Coats: Medallion Interior Latex Eggshell Paint

#### **Brick:**

1 Coat: Block filler  
1–2 Coats: Medallion Interior Latex Eggshell Paint

#### **Drywall:**

Prime with Medallion Interior Latex Eggshell Paint  
1–2 Coats: Medallion Interior Latex Eggshell Paint

#### **Cement:**

Prime with Medallion Interior Latex Eggshell Paint  
1–2 Coats: Medallion Interior Latex Eggshell Paint

#### **Metal:**

1 Coat: Valspar® Anti-Rust Primer  
1–2 Coats: Medallion Interior Latex Eggshell Paint

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Pigment Type:** Titanium Dioxide

**Viscosity:** 94–100 Krebs Units

**Sheen:** 10–20 Units @ 85° angle

**Flashpoint:** N/A

**VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 38%

**Weight Solids:** 52%

**Weight Per Gallon:** 10.9 lbs./gal.

**Practical Coverage:** Covers up to 400 ft<sup>2</sup> / gal (37 m<sup>2</sup>) depending on surface porosity.

**Thinning:** Thin only for spray application with up to 8 oz. of water per gallon of paint.

#### **Recommended Film Thickness:**

4.0 mil Wet      1.5 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 30–60 minutes

**Recoat:** 2–4 hours

**Washing Instructions:** Wait 7 days before washing with a mild detergent and soft sponge.

**Application Temperature:** 50–90°F (10–32°C)

**Storage Temperature:** 40–90°F (5–32°C)

### CERTIFICATIONS

Current as of: 8/7/2017

MPI #	N/A
MPI GPS 1	N/A
MPI GPS 2	N/A
UL Greenguard Gold	Yes
LEED (US)	Yes
LEED (Canada)	Yes

### REGULATORY COMPLIANCE

Current as of: 8/7/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes



### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime. Medallion® paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of Valspar® Medallion® Interior Latex Primer. For drastic color changes or deep, vivid colors, prime with Valspar® Medallion® Tintable Primer for optimal color accuracy and coverage.

#### **Plaster:**

Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Spot prime with before applying the finish coat.

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Spot prime new or bare surfaces before applying the finish coat.

#### **Brick:**

Masonry surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with Block Filler before applying the finish coat.

#### **Drywall/Wallboard:**

Fill cracks, pits and voids with patching compound, let cure and sand smooth. Remove all sanding dust. Spot prime new or bare surfaces before applying the finish coat.

#### **Cement/Concrete:**

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Spot prime soft concrete or masonry surfaces should before applying the finish coat.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights that vary from state to state.

### CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
877.825.7727  
valsparpaint.com  
Revised: 8/7/17  
Version: 4400F