



## Valspar® New Construction Primer



### Product Description

Interior Latex New Construction Primer is specifically designed to equalize surface texture differences between sanded tape joints and new drywall, resulting in an extremely uniform finish coat appearance. Ideal for airless spray application. Use on wallboard and tape joints in new construction or remodeling projects. Provides an excellent base coat for latex or oil-based paints. Formulated for professional painter use in residential, commercial, institutional and industrial applications.

### Features

- Ideal for new drywall
- Fast drying
- High hiding

### Recommended Uses

- Wallboard
- Drywall
- Tape joints
- Walls
- Under latex or oil-based paints

### Color and Base Information

	<b>oz./gal.</b>
White	128

### Shipping and Packaging

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:** Gallon – 4 per carton  
5-gallon pail

### Typical Properties (11287 White)

**Vehicle Type:** Vinyl Acrylic Resin

**Sheen:** 0–5 Units @ 85° angle

**Solids by Volume:** 28%

**Solids by Weight:** 45%

**Weight per Gallon:** 10.9 lbs./gal.

**VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Viscosity:** 105–111 Krebs units

**Dry Time:** 77 °F (25 °C) @ 50% relative humidity

**To the touch:** 30 minutes

**Recoat:** 2 –4 hours

**Surface Coverage:**

350–450 sq. ft./gal.

**At:** 4.0 mil wet, 1.1 mil dry

### Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

## Surface Preparation

Read the Lead Warning in the Cautions section. **New Drywall and Wallboard:** Sand tape joints smooth and even with the drywall or wallboard. Using a damp cloth or sponge, wipe tape joints and wallboard surfaces to remove all sanding dust. Be sure to remove all chalky residue before priming. Allow to dry, then prime.

**Previously Painted Surfaces:** Remove all dirt, dust, grease and oils by using a non-residue cleaner to clean the surface. Scrape off any loose, cracked or peeling paint. Patch cracks and nail holes. Sand smooth, then spot prime.

## Application and Clean-up

Paint only when surface and air temperatures are 50–90 °F (10 – 32 °C). Use paint paddle or mixing blade to stir paint thoroughly, bringing pigments to the top of the can. **Brush:** Use a premium quality polyester brush. **Roller:** Use a premium quality polyester roller with 1/2 to 3/4-inch nap. **Airless Spray:** Thinning is not usually necessary. Use 2000 PSI with a 0.015 to 0.021 tip. For airless spray, thin with up to 8 ounces of water per gallon – only if paint is too thick for sprayer. Clean up with warm, soapy water.

## Cautions (11287 White)

**WARNING!** Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. **WARNING:** This product contains chemicals known to the State of California to cause cancer. **FIRST AID: EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.\* **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **IF SWALLOWED:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

CL 3.3s

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
For additional safety and chronic health-hazard  
information, refer to the Material Safety Data  
Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Because application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product or a refund of its purchase price, at our option.